



## MULTI100 WIDE

### Typology

New generation LED lamps with SMD technology.

### Features

Matt diffusing cover; very wide light beam suitable for diffused lighting.

### Material

Thermally conductive compartment for housing the electronic components: optimization of heat dissipation and greater safety for the user.

### Notes

Do not use with dimmer.



220-240  
Vac

Ra 80





25000 h  
L70B50

IP20

GU10


-25°C  
+35°C



### Characteristic data

Power	4.6 W	Beam	100°	Dimmable	No	Input	220-240 Vac
Base	GU10	IP	20	Flux	650 lm	PF	0,5
Tc	4000 K	Ra	80	LED Warranty	G2	Axis	260 cd

### Dimensional characteristics



Ø	50 mm
H	55 mm

## Lighting and photometric features

Beam opening	100°
Flux	650 lm
CCT nominal colour temperature	4000 K
Colour of the light	Natural light
Colour rendering index	80
Lifespan	25000 h
LED lifespan	L70B50
Trigger time	<0,2 s
Heating time up to 60% of full efficiency	Instant Full Light
Mercury	0 mg

## Electrical characteristics

Rated power	4.6 W
Input voltage	220-240 Vac
Frequency	50 Hz
Dimmable	No
Power factor (PF)	0,5
Input current	0.039 A
Weighted energy consumption	5 kWh/1000h
Energy efficiency class	D
Number of cycles	100000
Operating temperature	-25°C / +35°C
Equivalence with incandescent lamp	77
Operating position	360°

## Photometry

	4000K	H(m)	D(m)	Emax(lx)
	Ra80		101°	
	Fixture Power	7W	1	2.42
	Source Flux	570lm	2	4.85
	Fixture Flux	570lm	3	7.27
	Efficacy	81lm/W	4	9.70
845780	Imax=397cd/klm	Imax	226cd	5
			12.12	9

EulumDat file on the site

## Other Infotech

Reflector	Yes
-----------	-----

## LED Warranty

G2	Up to 2 years (4000h/year) *4000h = 11h a day x 365 days. Without limitations on the duration of use for the first year, provided the observance of the installation conditions.
----	--

## European Directives

2009/125/EC \* Ecodesign  
 2011/65/EU \* RoHS  
 2012/19/EU \* RAEE  
 2014/30/EU \* EMC  
 2014/35/EU \* LVD  
 2015/863 \* Amending RoHS  
 2017/1369 \* Regulation for Energy Labelling  
 2019/2015 \* Regulation for Energy Labelling  
 2019/2020 \* Regulation for Ecodesign  
 2021/340 \* Amending Reg. Energy Labelling  
 2021/341 \* Amending Reg. Ecodesign

## Product standards

CEI EN 55015:2020 (+A11:2020)  
 CEI EN 60968:2016  
 CEI EN 61000-3-2:2019 (+A1:2021)  
 CEI EN 61000-3-3:2014 (+EC1:2014/+EC2:2016/+A1:2021/+A2:2022)  
 CEI EN 61547:2010  
 CEI EN 62031:2021 (+A11:2022)  
 CEI EN 62471:2010  
 IEC/TR 62471-2:2009  
 CEI EN 62560:2013 (+A1:2017/+A11:2020)  
 CEI 34-141:2014

## Logistics data

Item net weight	25 gr
Barcode single item	8011905845780
Number of pieces multiple pack	10
Barcode multiple pack	8011905845797
Minimum order quantity	10
Minimum packaging	10 / 10