



SLIMFLUX ROUND UP&DOWN SUSPENSION

Typology


Slim LED panel.

Features

TONDO TRASLUCIDE SUSPENSION: power supply unit integrated in ceiling rose. Fractioned by micro incisions on the panel, light is directed predominantly downwards while 30% of the light is projected upwards to create a striking effect that adds to any classic or modern environment. The power cable is one with the suspension cables, therefore invisible. Adjustable suspension wires: MAX 150 cm. Cable attachment with screw and steel cylinder.

Material


White painted metal body; frontal methacrylate panel.



Characteristic data

Power	40 W	Dimmable	No	Input	220-240 Vac	Base	Free Wire
IP	20	Flux	4000 lm	PF	0.95	Tc	4000 K
Ra	80	LED Warranty	G3	RG	RG0	Color	White

Dimensional characteristics



Ø	593 mm
L1	150 mm
H	19.5 mm


Lighting and photometric features

Flux	4000 lm
CCT nominal colour temperature	4000 K
Colour of the light	Natural light
Colour rendering index	80
Lifespan	30000 h
LED lifespan	L70B20
Trigger time	<0,2 s
Heating time up to 60% of full efficiency	Instant Full Light

Electrical characteristics

Rated power	40 W
Input voltage	220-240 Vac
Frequency	50/60 Hz
Dimmable	No
Power factor (PF)	0.95
Operating temperature	-25°C / +40°C

Photometry

	4000K	H(m)	D1(m)	D2(m)	Emax(lx)		
	Ra80		150°	149°			
	Fixture Power	40W	1	7.45	7.21	572	
	Source Flux	4000lm	2	14.89	14.42	143	
	Fixture Flux	4000lm	3	22.34	21.63	64	
	Efficacy	100lm/W	4	29.78	28.83	36	
	984274	I _{max} =163cd/klm	I _{max}	653cd	5	37.23	36.04

EulumDat file on the site

Other Infotech

Flicker Free	Yes
--------------	-----

LED Warranty

G3	Up to 3 years (4000h/year) *4000h = 11h a day x 365 days. Without limitations on the duration of use for the first year, provided the observance of the installation conditions.
----	--

European Directives

2009/125/EC * Ecodesign
2011/65/EU * RoHS
2012/19/EU * RAEE
2014/30/EU * EMC
2014/35/EU * LVD
2015/863 * Amending RoHS
2017/1369 * Regulation for Energy Labelling
2019/2015 * Regulation for Energy Labelling
2019/2020 * Regulation for Ecodesign
2021/340 * Amending Reg. Energy Labelling
2021/341 * Amending Reg. Ecodesign

Product standards

CEI EN 55015:2020 (+A11:2020)
CEI EN 60598-1:2022
CEI EN 60598-2-1:2022
CEI EN 61000-3-2:2019 (+A1:2021)
CEI EN 61000-3-3:2014 (+EC1:2014/+EC2:2016/+A1:2021/+A2:2022)
CEI EN 61547:2010
CEI EN 62031:2021 (+A11:2022)
CEI EN 62471:2010
IEC/TR 62471-2:2009
CEI EN 62493:2015
CEI 34-141:2014

Logistics data

Item net weight	2600 gr
Barcode single item	8011905984311
Number of pieces multiple pack	5
Barcode multiple pack	8011905985752
Minimum order quantity	1
Minimum packaging	1 / 5