



TRI-PROOF S2T

Typology

Linear TRI-PROOF luminaire for surface or suspended installations.

Features

Complete with G13 lamp holders for use with 2 replaceable T8 LED tubes.
Quick opening mechanism for wiring.
Easy to connect in series thanks to the quick spring clamp supplied.

Installation

Steel brackets for ceiling anchoring or suspension.

Material

ABS GW TEST 650°C body and closing hinges; polystyrene (PS) screen.

Applications

Production areas, car parks, laboratories and warehouses.

BASIC

220-240
Vac



IP65

IK04

G13


-25°C
+35°C



Characteristic data

Dimmable	No	Input	220-240 Vac	Base	G13	IP	65
LED Warranty	G2	IK	IK04				

Dimensional characteristics



L	1263 mm
L1	108 mm
H	90 mm

Electrical characteristics

Input voltage	220-240 Vac
Dimmable	No
Operating temperature	-25°C / +35°C

LED Warranty

G2	Up to 2 years (4000h/year) *4000h = 11h a day x 365 days. Without limitations on the duration of use for the first year, provided the observance of the installation conditions.
----	--

Logistics data

Barcode single item	8011905987848
Number of pieces multiple pack	8
Barcode multiple pack	8011905988050
Minimum order quantity	8