



## BATTEN BT3

### Typology

Linear ceiling fixture equipped with high efficiency LED sources.  
Fitted with a quick spring clamp for connection in series.

### Features

Quick opening mechanism for wiring.  
Easy to connect in series thanks to the quick spring clamp supplied.  
Can be used in series of up to 22 fixtures for the 18 W model, 11 fixtures for the 34 W model and up to 7 fixtures for the 50 W model.

### Installation

"Snap on" AISI 316 stainless steel brackets for ceiling or suspension installation.  
Every batten is equipped with brackets.  
Adjustable suspension cables available as a separate code.

### Material

Polycarbonate body: opal polycarbonate screen equipped with internal fins for flow recovery and emission optimization.

### Applications

Supermarkets, car parks, laboratories, warehouses.



220-240  
Vac

Ra >80



50000 h  
L70B20


IP65

IK08

Screws

-25°C  
+35°C

Risk  
Group 1



### Characteristic data

Power	34 W	Beam	120°	Dimmable	No	Input	220-240 Vac
Base	Screws	IP	65	Flux	4300 lm	PF	0,90
Tc	4000 K	Ra	>80	LED Warranty	G5h24	IK	IK08
RG	RG1	Color	White				

## Dimensional characteristics



L	1200 mm
L1	63 mm
H	63 mm

## Lighting and photometric features

Beam opening	120°
Flux	4300 lm
CCT nominal colour temperature	4000 K
Colour of the light	Natural light
Colour rendering index	>80
Lifespan	50000 h
LED lifespan	L70B20
Trigger time	<0,2 s
Heating time up to 60% of full efficiency	Instant Full Light

## Electrical characteristics

Rated power	34 W
Input voltage	220-240 Vac
Frequency	50/60 Hz
Dimmable	No
Power factor (PF)	0,90
Weighted energy consumption	34 kWh/1000h
Number of cycles	100000
Operating temperature	-25°C / +35°C

## Photometry

	4000K	H(m)	D1(m)	D2(m)	Emax(lx)		
	Ra80		115°	140°			
	Fixture Power	34W	1	3.17	5.51	1093	
	Source Flux	4300lm	2	6.34	11.03	273	
	Fixture Flux	4300lm	3	9.51	16.54	121	
	Efficacy	126lm/W	4	12.67	22.05	68	
	941116	Imax=255cd/klm	Imax	1095cd	5	15.84	27.56

EuLumDat file on the site

## LED Warranty

65h24	Full Guarantee 5 years (24h/24h) Without limitations on the duration of use for the first year, provided the observance of the installation conditions.
-------	---

## European Directives

2009/125/EC \* Ecodesign  
2011/65/EU \* RoHS  
2012/19/EU \* RAEE  
2014/30/EU \* EMC  
2014/35/EU \* LVD  
2015/863 \* Amending RoHS  
2017/1369 \* Regulation for Energy Labelling  
2019/2015 \* Regulation for Energy Labelling  
2019/2020 \* Regulation for Ecodesign  
2021/340 \* Amending Reg. Energy Labelling  
2021/341 \* Amending Reg. Ecodesign

## Product standards

CEI EN 55015:2020 (+A11:2020)  
CEI EN 60598-1:2022  
CEI EN 60598-2-1:2022  
CEI EN 61000-3-2:2019 (+A1:2021)  
CEI EN 61000-3-3:2014 (+EC1:2014/+EC2:2016/+A1:2021/+A2:2022)  
CEI EN 61547:2010  
CEI EN 62031:2021 (+A11:2022)  
CEI EN 62471:2010  
IEC/TR 62471-2:2009  
CEI EN 62493:2015  
CEI 34-141:2014

## Logistics data

Item net weight	850 gr
Barcode single item	8011905941116
Number of pieces multiple pack	10
Barcode multiple pack	8011905959142
Minimum order quantity	1
Minimum packaging	1 / 10