



SURFACE PROFILES: P04B

Features

Profile for surface or recessed installation with limited width.

CAN BE USED WITH LED STRIPS WITH MAXIMUM WIDTH:

20 mm

MAXIMUM POWER:

30W/m

Installation

Surface or recessed.

Cabling can be in line with the profile or exit the bottom of the profile or on the side.

Material

6063 aluminium profile with white PMMA screen.

Accessories

Every 3 metre bar is complete with 3 sets of end caps (with and without hole) and 3 sets of mounting clips.


Packaging

Supplied in minimum packages of 5 bars, each one measuring 3 meters complete with screen and accessories.

Spare accessories for additional cutting available with a separate code.

-15°C
+35°C

Dimensional characteristics



| | |
|----|---------|
| L | 3000 mm |
| L1 | 26.6 mm |
| H | 15.5 mm |

Electrical characteristics

| | |
|-----------------------|---------------|
| Operating temperature | -15°C / +35°C |
|-----------------------|---------------|

European Directives

| | |
|---|--|
| 2011/65/EU * RoHS 2015/863 * Amending RoHS | |
|---|--|

Logistics data

| | |
|--------------------------------|---------------|
| Barcode single item | 8011905912369 |
| Number of pieces multiple pack | 5 |