



## HELIOS IP65

### Typology

High efficiency SMD LED sources LED source integrated in a Class III, IP65, Ra90, 50000 hours downlight fixture.

### Features

IP65 fixture both optical/front side and the back/ component side; IP20 remote driver included in the package.  
Soft satin effect polycarbonate anti-glare diffuser.

### Installation

Complete with springs for easy fastening into false ceilings.  
Cable (1 m) with IP65 quick connector.

### Material

Aluminium finned dissipation body.

### Notes


Providing greater visual comfort, improved definition of detail and reduction of stress.



### Characteristic data

Power	40 W	Beam	90°	Dimmable	No	Input	220-240 Vac
Base	Wire	IP	65	Optical compartment IP	43	Flux	3200 lm
Axis	1400 cd	PF	0,9	Tc	4000 K	Ra	>90
LED Warranty	G5h24	RG	RG1				

### Dimensional characteristics



Ø	230 mm
H	73 mm

Cutting hole	210
--------------	-----

## Lighting and photometric features

Beam opening	90°
Flux	3200 lm
Axis	1400 cd
CCT nominal colour temperature	4000 K
Colour of the light	Natural light
Colour rendering index	>90
Lifespan	50000 h
LED lifespan	L70B20
Trigger time	<0,2 s
Heating time up to 60% of full efficiency	Instant Full Light

## Electrical characteristics

Rated power	40 W
Input voltage	220-240 Vac
Frequency	50/60 Hz
Dimmable	No
Power factor (PF)	0,9
Weighted energy consumption	40 kWh/1000h
Number of cycles	100000
Operating temperature	-25°C / +45°C

## Photometry

	4000K	H(m)	D(m)	Emax(lx)	
	Ra90		94°		
	Fixture Power	40W	1	2.14	1406
	Source Flux	3200lm	2	4.27	351
	Fixture Flux	3200lm	3	6.41	156
	Efficacy	80lm/W	4	8.54	88
	937423 I <sub>max</sub> =439cd/klm	I <sub>max</sub>	1406cd	5	10.68

EulumDat file on the site

## Other Infotech

Flicker Free	Yes
--------------	-----

## LED Warranty

G5h24	Full Guarantee 5 years (24h/24h) Without limitations on the duration of use for the first year, provided the observance of the installation conditions.
-------	---

## European Directives

2009/125/EC \* Ecodesign  
2011/65/EU \* RoHS  
2012/19/EU \* RAEE  
2014/30/EU \* EMC  
2014/35/EU \* LVD  
2015/863 \* Amending RoHS  
2017/1369 \* Regulation for Energy Labelling  
2019/2015 \* Regulation for Energy Labelling  
2019/2020 \* Regulation for Ecodesign  
2021/340 \* Amending Reg. Energy Labelling  
2021/341 \* Amending Reg. Ecodesign

## Product standards

CEI EN 55015:2020 (+A11:2020)  
CEI EN 60598-1:2022  
CEI EN 60598-2-2:2012  
CEI EN 61000-3-2:2019 (+A1:2021)  
CEI EN 61000-3-3:2014 (+EC1:2014/+EC2:2016/+A1:2021/+A2:2022)  
CEI EN 61547:2010  
CEI EN 62031:2021 (+A11:2022)  
CEI EN 62471:2010  
IEC/TR 62471-2:2009  
CEI EN 62493:2015  
CEI 34-141:2014

## Logistics data

Item net weight	240 gr
Barcode single item	8011905937423
Number of pieces multiple pack	12
Barcode multiple pack	8011905938499
Minimum order quantity	1