



CIRCOLINA 32

Typology

Compact, circular and linear fluorescent lamps.

Features

The best fluorescent and triphosphorous powders for maximum light colour control and light emission over time, good colour rendering and the excellent luminous efficiency.

A wide reliable range for installation in professional contexts such and home environments.

86,7 Vac

Ra >80




8000 h

IP20

G10q


-15°C
+35°C



Characteristic data

Power	32 W	Dimmable	No	Input	86,7 Vac	Base	G10q
IP	20	Flux	2315 lm	Tc	4100 K	Ra	>80

Dimensional characteristics



Ø	300 mm
L2	29 mm

Lighting and photometric features

Flux	2315 lm
CCT nominal colour temperature	4100 K
Colour of the light	Natural light
Colour rendering index	>80
Lifespan	8000 h
Luminous Flux Maintenance at 2000h	88
Luminous Flux Maintenance at 4000h	85
Luminous Flux Maintenance at 6000h	80
Luminous Flux Maintenance at 8000h	75
Luminous Flux Maintenance at 12000h	72
Luminous Flux Maintenance at 16000h	70
Lamp survival factor at 2000h	100
Lamp survival factor at 4000h	100
Lamp survival factor at 6000h	95
Lamp survival factor at 8000h	80
Lamp survival factor at 12000h	45

Electrical characteristics

Rated power	32 W
Input voltage	86,7 Vac
Frequency	50 Hz
Dimmable	No
Energy efficiency class	G
Operating temperature	-15°C / +35°C

Standards and Directives

2006/95/CE * Bassa Tensione	IEC/TR 62471-2
2004/108/CE * Compatibilità Elettromagnetica	EN 62031 * anno 2009 (+A1:2013)
2011/65/UE * RoHS	EN 62560 * anno 2013
2012/19/UE * RAEE	EN 60968 * anno 2013
EN 61547 * anno 2010	2010/30/EU * Energy Consumption
EN 55015 * anno 2014	874/2012 * Regulation for Energy Labelling
EN 61000-3-2 * anno 2007 (+A1/+A2:2011)	2009/125/CE * Progettazione Eco Compatibile
EN 61000-3-3 * anno 2014	1194/2012 * Progettazione Eco Compatibile
EN 62471 * anno 2010	

Logistics data

Item net weight	190 gr
Barcode single item	8011905854331
Number of pieces multiple pack	12
Barcode multiple pack	8011905854348