



HELIOS UGR RECESSED FIXTURES

Typology

LED source with COB technology and an integrated high efficiency chip in a low glare UGR recessed light fixture.
Remote driver.

Features

The deep recess of the light source combined with the advanced lens technology ensures glare ratings from UGR<11 to UGR<19, applications include offices or places of work where computer screens are used and low glare is essential.
A sealed light source provides easy maintenance and cleaning.

Installation

Complete with springs for easy fastening into false ceilings.

Material

Aluminium body; extremely light and easy to manoeuvre.

Notes

Providing greater visual comfort, improved definition of detail and reduction of stress.

PRO	220-240 Vac	Ra >90		50000 h L80B20	IP20 VI IP43 VO	Wire	-25°C +45°C	Risk Group 1	UGR <15
		FLICKER FREE							

Characteristic data

Power	14 W	Beam	36°	Dimmable	No	Input	220-240 Vac
Base	Wire	IP	20	Optical compartment IP	43	Flux	1450 lm
Axis	3800 cd	PF	0,95	UGR	<15	Tc	3000 K
Ra	>90	LED Warranty	G5h24	RG	RG1		

Dimensional characteristics



Ø	118 mm
H	60 mm

Cutting hole	100
--------------	-----

Lighting and photometric features

Beam opening	36°
Flux	1450 lm
Axis	3800 cd
CCT nominal colour temperature	3000 K
Colour of the light	Warm light
Colour rendering index	>90
Lifespan	50000 h
LED lifespan	L80B20
Trigger time	<0,2 s
Heating time up to 60% of full efficiency	Instant Full Light
UGR	<15

Electrical characteristics

Rated power	14 W
Input voltage	220-240 Vac
Frequency	50/60 Hz
Dimmable	No
Power factor (PF)	0,95
Weighted energy consumption	14 kWh/1000h
Number of cycles	100000
Operating temperature	-25°C / +45°C

Photometry

	3000K	H(m)	D(m)	Emax(lx)		
	Ra90		34°			
	Fixture Power	14W	1	0.61	3807	
	Source Flux	1450lm	2	1.21	952	
	Fixture Flux	1450lm	3	1.82	423	
	Efficacy	104lm/W	4	2.42	238	
	936815	Imax=2626cd/klm	Imax	3807cd	5	3.03

EulumDat file on the site

Other Infotech

Flicker Free	Yes
--------------	-----

LED Warranty

G5h24	Full Guarantee 5 years (24h/24h) Without limitations on the duration of use for the first year, provided the observance of the installation conditions.
-------	---

European Directives

2009/125/EC * Ecodesign
2011/65/EU * RoHS
2012/19/EU * RAEE
2014/30/EU * EMC
2014/35/EU * LVD
2015/863 * Amending RoHS
2017/1369 * Regulation for Energy Labelling
2019/2015 * Regulation for Energy Labelling
2019/2020 * Regulation for Ecodesign
2021/340 * Amending Reg. Energy Labelling
2021/341 * Amending Reg. Ecodesign

Product standards

CEI EN 55015:2020 (+A11:2020)
CEI EN 60598-1:2022
CEI EN 60598-2-2:2012
CEI EN 61000-3-2:2019 (+A1:2021)
CEI EN 61000-3-3:2014 (+EC1:2014/+EC2:2016/+A1:2021/+A2:2022)
CEI EN 61547:2010
CEI EN 62031:2021 (+A11:2022)
CEI EN 62471:2010
IEC/TR 62471-2:2009
CEI EN 62493:2015
CEI 34-141:2014

Logistics data

Item net weight	100 gr
Barcode single item	8011905936815
Number of pieces multiple pack	50
Minimum order quantity	1
Minimum packaging	1 / 50