



## DRIVER FOR DURASTRIP 24V

### Features

Driver for LED strips.  
SELV equivalent; protection device in case of short circuit or overload in the secondary circuit.  
24V drivers have loose wires connection and are TUV marked.

### Notes

Output voltage fine control option.

220-240  
Vac


50000 h

IP67

-25°C  
+35°C

FLICKER  
FREE


### Characteristic data

Power	80 W	Dimmable	TRIAC/LEADING EDGE	Input	220-240 Vac	IP	67
PF	0,9	LED Warranty	G5h24				

### Dimensional characteristics

L	200 mm
L1	70 mm
H	42 mm

### Lighting and photometric features

Lifespan	50000 h
----------	---------

### Electrical characteristics

Rated power	80 W
Input voltage	220-240 Vac
Frequency	50/60 Hz
Output voltage	24 Vdc
Dimmable	TRIAC/LEADING EDGE
Power factor (PF)	0,9
Input current	4 A
Max output current	3300 mA
Operating temperature	-25°C / +35°C

## Other Infotech

Flicker Free	Yes
Max Case Temperature	90

## LED Warranty

G5h24	Full Guarantee 5 years (24h/24h) Without limitations on the duration of use for the first year, provided the observance of the installation conditions.
-------	---

## European Directives

2009/125/EC \* Ecodesign  
2011/65/EU \* RoHS  
2012/19/EU \* RAEE  
2014/30/EU \* EMC  
2014/35/EU \* LVD  
2015/863 \* Amending RoHS  
2017/1369 \* Regulation for Energy Labelling  
2019/2015 \* Regulation for Energy Labelling  
2019/2020 \* Regulation for Ecodesign  
2021/340 \* Amending Reg. Energy Labelling  
2021/341 \* Amending Reg. Ecodesign

## Product standards

CEI EN 55015:2020 (+A11:2020)  
CEI EN 61000-3-2:2019 (+A1:2021)  
CEI EN 61000-3-3:2014 (+EC1:2014/+EC2:2016/+A1:2021/+A2:2022)  
CEI EN 61347-1:2016 (+A1:2021)  
CEI EN 61347-2-13:2015 (+A1:2018)  
CEI EN 61547:2010

## Logistics data

Item net weight	900 gr
Barcode single item	8011905983178
Minimum order quantity	1
Minimum packaging	1 / 1