

## Characteristic data

Input	220-240 Vac	Base	GU10	IP	20	Optical compartment IP	23
LED Warranty	G5h24	Color	Silver gray				

## MULTI-OPTIC RECESSED FIXTURE

### Typology

Rectangular recessed fixture for two adjustable GU10 lamps.

### Features

Widely used in retail installations, it meets the needs of those who prefer a recessed ceiling luminaire with replaceable lamps. It offers the advantage of having both multidirectional and adjustable light beams from + 15 ° to -15 ° in the vertical plane. Houses PAR16 lamps; compatible with all GU10 lamps in the Duralamp catalogue. Max 30 W.


### Installation

Recessed with the special galvanised aluminium springs. Complete with GU10 lamp holder.

### Material

Body in black painted aluminium with silver colour frame.

## Dimensional characteristics



L	107 mm
L1	202 mm
H	110 mm

Cutting hole	95x190
--------------	--------

## Electrical characteristics

Input voltage	220-240 Vac
Frequency	50/60 Hz
Operating temperature	-25°C / +45°C

## LED Warranty

G5h24	Full Guarantee 5 years (24h/24h) Without limitations on the duration of use for the first year, provided the observance of the installation conditions.
-------	---

## European Directives

2009/125/EC \* Ecodesign  
2011/65/EU \* RoHS  
2012/19/EU \* RAEE  
2014/30/EU \* EMC  
2014/35/EU \* LVD  
2015/863 \* Amending RoHS  
2017/1369 \* Regulation for Energy Labelling  
2019/2015 \* Regulation for Energy Labelling  
2019/2020 \* Regulation for Ecodesign  
2021/340 \* Amending Reg. Energy Labelling  
2021/341 \* Amending Reg. Ecodesign

## Product standards

CEI EN 55015:2020 (+A11:2020)  
CEI EN 60598-1:2022  
CEI EN 60598-2-2:2012  
CEI EN 61000-3-2:2019 (+A1:2021)  
CEI EN 61000-3-3:2014 (+EC1:2014/+EC2:2016/+A1:2021/+A2:2022)  
CEI EN 61547:2010  
CEI EN 62031:2021 (+A11:2022)  
CEI EN 62471:2010  
IEC/TR 62471-2:2009  
CEI EN 62493:2015  
CEI 34-141:2014

## Logistics data

Item net weight	335 gr
Barcode single item	8011905935269
Number of pieces multiple pack	10
Barcode multiple pack	8011905938444
Minimum order quantity	1
Minimum packaging	1 / 10

All parts of this document are Duralamp ownership. All rights reserved. This document and the included information are provided without any responsibility deriving from mistakes or omissions. No part of this document can be cut, reproduced or used without written authorization. Duralamp maintains the right to change the included data without notice due to improvements of the products