



MULTICURRENT DRIVER

**Features**  
Can be used with fittings with replaceable remote driver.  
220÷240 V 50/60 Hz  
Lifetime 50000 h.  
Available with 100-240V voltage upon request.

220-240  
Vac

100000 h

IP20

-20°C  
+45°C

SELV

FLICKER  
FREE

Characteristic data

Power	40 W	Dimmable	No	Input	220-240 Vac	IP	20
PF	0.95	LED Warranty	G5h24				

Dimensional characteristics

L	142 mm
L1	50 mm
H	30 mm

Lighting and photometric features

Lifespan	100000 h
----------	----------

Electrical characteristics

Rated power	40 W
Input voltage	220-240 Vac
Output voltage	28-42 Vdc
Dimmable	No
Power factor (PF)	0.95
Input current	0.35 A
Operating temperature	-20°C / +45°C

## Other Infotech

Flicker Free	Yes
Max Case Temperature	90

## LED Warranty

G5h24	Full Guarantee 5 years (24h/24h) Without limitations on the duration of use for the first year, provided the observance of the installation conditions.
-------	---------------------------------------------------------------------------------------------------------------------------------------------------------------

## European Directives

2009/125/EC \* Ecodesign  
2011/65/EU \* RoHS  
2012/19/EU \* RAEE  
2014/30/EU \* EMC  
2014/35/EU \* LVD  
2015/863 \* Amending RoHS  
2017/1369 \* Regulation for Energy Labelling  
2019/2015 \* Regulation for Energy Labelling  
2019/2020 \* Regulation for Ecodesign  
2021/340 \* Amending Reg. Energy Labelling  
2021/341 \* Amending Reg. Ecodesign

## Product standards

CEI EN 55015:2020 (+A11:2020)  
CEI EN 61000-3-2:2019 (+A1:2021)  
CEI EN 61000-3-3:2014 (+EC1:2014/+EC2:2016/+A1:2021/+A2:2022)  
CEI EN 61347-1:2016 (+A1:2021)  
CEI EN 61347-2-13:2015 (+A1:2018)  
CEI EN 61547:2010

## Logistics data

Item net weight	150 gr
Barcode single item	8015466162270
Minimum order quantity	1
Minimum packaging	1 / 1