



## DECOS LED TECNO VINTAGE MIRROR TOP GLS

### Typology

Range of lamps "filament LED": micro-led sources - that optimise thermal management - are positioned on a glass support and completely covered with phosphor powder that unifies, amplifies and diffuses the light.

### Features





Excellent colour maintenance and are light constant over time. The spectrum of Tecno Vintage lamps is particularly rich in the warm colour bands to obtain an effect as close as possible to that of the lamps to be replaced.

### Material

Glass bulb.

### Notes


Do not use with dimmers except if otherwise indicated.



### Characteristic data

|       |        |      |      |              |        |       |             |
|-------|--------|------|------|--------------|--------|-------|-------------|
| Power | 4 W    | Beam | 180° | Dimmable     | No     | Input | 220-240 Vac |
| Base  | E27    | IP   | 20   | Flux         | 400 lm | PF    | 0,50        |
| Tc    | 2600 K | Ra   | 80   | LED Warranty | G2     | Color | Gold        |

### Dimensional characteristics



|   |        |
|---|--------|
| Ø | 60 mm  |
| H | 105 mm |

## Lighting and photometric features

|   |                    |
|---|--------------------|
| Beam opening                              | 180°               |
| Flux                                      | 400 lm             |
| CCT nominal colour temperature            | 2600 K             |
| Colour of the light                       | Warm light         |
| Colour rendering index                    | 80                 |
| Lifespan                                  | 15000 h            |
| LED lifespan                              | L70B50             |
| Trigger time                              | <0,2 s             |
| Heating time up to 60% of full efficiency | Instant Full Light |
| Mercury                                   | 0 mg               |

## Electrical characteristics

|                                    |               |
|------------------------------------|---------------|
| Rated power                        | 4 W           |
| Input voltage                      | 220-240 Vac   |
| Frequency                          | 50 Hz         |
| Dimmable                           | No            |
| Power factor (PF)                  | 0,50          |
| Weighted energy consumption        | 4 kWh/1000h   |
| Energy efficiency class            | F             |
| Number of cycles                   | 100000        |
| Operating temperature              | -25°C / +35°C |
| Equivalence with incandescent lamp | 35            |
| Operating position                 | 360°          |

## LED Warranty

|    |  |
|----|--|
| G2 | Up to 2 years<br>(4000h/year) *4000h = 11h a day x 365 days.<br>Without limitations on the duration of use for the first year, provided the observance of the installation conditions. |
|----|--|

## European Directives

2009/125/EC \* Ecodesign  
2011/65/EU \* RoHS  
2012/19/EU \* RAEE  
2014/30/EU \* EMC  
2014/35/EU \* LVD  
2015/863 \* Amending RoHS  
2017/1369 \* Regulation for Energy Labelling  
2019/2015 \* Regulation for Energy Labelling  
2019/2020 \* Regulation for Ecodesign  
2021/340 \* Amending Reg. Energy Labelling  
2021/341 \* Amending Reg. Ecodesign

## Product standards

CEI EN 55015:2020 (+A11:2020)  
CEI EN 60968:2016  
CEI EN 61000-3-2:2019 (+A1:2021)  
CEI EN 61000-3-3:2014 (+EC1:2014/+EC2:2016/+A1:2021/+A2:2022)  
CEI EN 61547:2010  
CEI EN 62031:2021 (+A11:2022)  
CEI EN 62471:2010  
IEC/TR 62471-2:2009  
CEI EN 62560:2013 (+A1:2017/+A11:2020)  
CEI 34-141:2014

## Logistics data

|                                |               |
|--------------------------------|---------------|
| Item net weight                | 30 gr         |
| Barcode single item            | 8011905922481 |
| Number of pieces multiple pack | 10            |
| Minimum order quantity         | 10            |
| Minimum packaging              | 10 / 10       |

All parts of this document are Duralamp ownership. All rights reserved. This document and the included information are provided without any responsibility deriving from mistakes or omissions. No part of this document can be cut, reproduced or used without written authorization. Duralamp maintains the right to change the included data without notice due to improvements of the products