

## LESELI-Q PRO TRACK

### Typology

High efficiency SMD LED sources integrated into the body of the light fixture available in 3 different versions: recessed, ceiling for surface installation and with a track attachment.

### Features

The possibility to use the same fixture with different installation types makes it possible to maintain a uniform aesthetic in different areas of the same space.

### Installation

Recessed: with a rapid fixing system to attach to the plasterboard ceiling using springs, electrical connection and free wires.

Surface-mounted: with the frame code PLAFOW1SQ-W, free terminals electrical connection.

Track version: code W1SQT30-W complete with eurostandard compatible adapter.

### Material

High dissipation die-cast aluminum body with antiyellowing PC screen: white painted aluminum frame.

### Notes

Luminaire is Non-Dimming.

Providing greater visual comfort, improved definition of detail and reduction of stress.



Ra >85



50000 h  
L70B20

IP20 VI  
IP43 VO

For track

Risk  
Group 0



120°


FLICKER  
FREE



### Characteristic data

Power	26 W	Beam	120°	Dimmable	No	Base	For track
IP	20	Optical compartment IP	43	Flux	2000 lm	PF	0,9
Tc	3000 K	Ra	>85	LED Warranty	G5h24	RG	RG0

## Dimensional characteristics



L	223 mm
H	43 mm

## Lighting and photometric features

Beam opening	120°
Flux	2000 lm
CCT nominal colour temperature	3000 K
Colour of the light	Warm light
Colour rendering index	>85
Lifespan	50000 h
LED lifespan	L70B20
Trigger time	<0,2 s
Heating time up to 60% of full efficiency	Instant Full Light

## Electrical characteristics

Rated power	26 W
Dimmable	No
Power factor (PF)	0,9

## Photometry

	3000K	H(m)	D(m)	Emax(lx)
	Ra85		113°	
Fixture Power	26W	1	3.01	694
Source Flux	2000lm	2	6.02	173
Fixture Flux	2000lm	3	9.02	77
Efficacy	77lm/W	4	12.03	43
Imax=347cd/klm	Imax	5	15.04	28

EulumDat file on the site

## Other Infotech

Flicker Free	Yes
--------------	-----

## LED Warranty

G5h24	Full Guarantee 5 years (24h/24h) Without limitations on the duration of use for the first year, provided the observance of the installation conditions.
-------	---

## European Directives

2009/125/EC \* Ecodesign  
 2011/65/EU \* RoHS  
 2012/19/EU \* RAEE  
 2014/30/EU \* EMC  
 2014/35/EU \* LVD  
 2015/863 \* Amending RoHS  
 2017/1369 \* Regulation for Energy Labelling  
 2019/2015 \* Regulation for Energy Labelling  
 2019/2020 \* Regulation for Ecodesign  
 2021/340 \* Amending Reg. Energy Labelling  
 2021/341 \* Amending Reg. Ecodesign

## Product standards

CEI EN 55015:2020 (+A11:2020)  
 CEI EN 60598-1:2022  
 CEI EN 60598-2-1:2022  
 CEI EN 61000-3-2:2019 (+A1:2021)  
 CEI EN 61000-3-3:2014 (+EC1:2014/+EC2:2016/+A1:2021/+A2:2022)  
 CEI EN 61547:2010  
 CEI EN 62031:2021 (+A11:2022)  
 CEI EN 62471:2010  
 IEC/TR 62471-2:2009  
 CEI EN 62493:2015  
 CEI 34-141:2014

## Logistics data

Barcode single item	8011905955601
Minimum order quantity	1