



## MINILINI

### Typology

Minilini is a mains voltage architectural linear projector for surface mounted installation.

### Features

It is constructed from extruded aluminium with an opal polycarbonate cover and is rated IP65 making it suitable for exterior environments: 40 mm wide and 301 , 595 or 1146 mm long and available in various beam angles and wattages. Accessories include a selection of fixed and angled surface mounting brackets providing installation uniformity or adjustable brackets for further flexibility. Minilini is complete with integrated protection from voltage spikes.

### Installation

Choice of surface mounting brackets with different fixed angles - 15°, 30°, 45° - or with adjustable brackets of different heights to be ordered with separate codes.

### Usage information

230V: Dimmable 10-100%, TRIAC Leading edge

120V: ELV

### Colour of the light

Choice of white colour temperatures.

### Binning

ANSI/SDCM: 2 step.

2700K - 3000K - 3500K

### Connections

Maximum connection length: 18 modules for the 16W version; 9 modules for the 32W version, 4 modules for the 64W version.



220-240  
Vac

Ra >90



50000 h  
L70B20

IP65

Risk  
Group 1



110°



### Characteristic data

Power	32 W	Beam	110°	Dimmable	Yes	Input	220-240 Vac
IP	65	Flux	1390 lm	Tc	3000 K	Ra	>90
LED Warranty	G5h24	Axis	480 cd	RG	RG1		

## Dimensional characteristics



L	591 mm
L1	40 mm
H	40 mm

## Lighting and photometric features

Beam opening	110°
Flux	1390 lm
CCT nominal colour temperature	3000 K
Colour of the light	Warm light
Colour rendering index	>90
Lifespan	50000 h
LED lifespan	L70B20

## Electrical characteristics

Rated power	32 W
Input voltage	220-240 Vac
Frequency	50 Hz
Dimmable	Yes
Weighted energy consumption	32 kWh/1000h

## Photometry

	3000K	H(m)	D(m)	Emax(lx)		
	Ra90		112°			
	Fixture Power	32W	1	2.95	489	
	Source Flux	1390lm	2	5.89	122	
	Fixture Flux	1390lm	3	8.84	54	
	Efficacy	43lm/W	4	11.78	31	
955335	Imax=352cd/klm	Imax	489cd	5	14.73	20

EulumDat file on the site

## LED Warranty

G5h24	<p>Full Guarantee</p> <p>5 years</p> <p>(24h/24h) Without limitations on the duration of use for the first year, provided the observance of the installation conditions.</p>
-------	--

## European Directives

2009/125/EC \* Ecodesign  
 2011/65/EU \* RoHS  
 2012/19/EU \* RAEE  
 2014/30/EU \* EMC  
 2014/35/EU \* LVD  
 2015/863 \* Amending RoHS  
 2017/1369 \* Regulation for Energy Labelling  
 2019/2015 \* Regulation for Energy Labelling  
 2019/2020 \* Regulation for Ecodesign  
 2021/340 \* Amending Reg. Energy Labelling  
 2021/341 \* Amending Reg. Ecodesign

## Product standards

CEI EN 55015:2020 (+A11:2020)  
 CEI EN 60598-1:2022  
 CEI EN 60598-2-5:2016  
 CEI EN 61000-3-2:2019 (+A1:2021)  
 CEI EN 61000-3-3:2014 (+EC1:2014/+EC2:2016/+A1:2021/+A2:2022)  
 CEI EN 61547:2010  
 CEI EN 62031:2021 (+A11:2022)  
 CEI EN 62471:2010  
 IEC/TR 62471-2:2009  
 CEI EN 62493:2015  
 CEI 34-141:2014

## Logistics data

Barcode single item	8011905955335
Minimum order quantity	1