



## STAGNA S2T L2 IP65 - 50000H

### Typology

Waterproof linear ceiling light with G13 connection for 2 TUBOLED.  
Complete with 50,000h Tuboled.

### Features

Quick opening mechanism for wiring.  
Designed to withstand dust and water jets.

### Installation

"Snap on" AISI 316 stainless steel brackets for ceiling or suspension installation.  
Every batten is equipped with brackets.

### Material

Polycarbonate body and transparent polycarbonate screen.



### Characteristic data

|       |      |              |         |       |             |      |        |
|-------|------|--------------|---------|-------|-------------|------|--------|
| Power | 40 W | Dimmable     | No      | Input | 220-240 Vac | Base | G13    |
| IP    | 65   | Flux         | 3700 lm | PF    | 0,9         | Tc   | 4000 K |
| Ra    | >80  | LED Warranty | G4      | IK    | IK07        | RG   | RG0    |

### Dimensional characteristics



|    |         |
|----|---------|
| L  | 1575 mm |
| L1 | 95 mm   |
| H  | 60 mm   |

## Lighting and photometric features

|                                |         |
|--------------------------------|---------|
| Flux                           | 3700 lm |
| CCT nominal colour temperature | 4000 K  |
| Colour rendering index         | >80     |
| Lifespan                       | 50000 h |
| LED lifespan                   | L70B50  |

## Electrical characteristics

|                       |               |
|-----------------------|---------------|
| Rated power           | 40 W          |
| Input voltage         | 220-240 Vac   |
| Frequency             | 50-60 Hz      |
| Dimmable              | No            |
| Power factor (PF)     | 0,9           |
| Operating temperature | -25°C / +35°C |

## Photometry

EulumDat file on the site

## LED Warranty

|    |           |
|----|-----------|
| G4 | undefined |
|----|-----------|

## European Directives

2009/125/EC \* Ecodesign  
 2011/65/EU \* RoHS  
 2012/19/EU \* RAEE  
 2014/30/EU \* EMC  
 2014/35/EU \* LVD  
 2015/863 \* Amending RoHS  
 2017/1369 \* Regulation for Energy Labelling  
 2019/2015 \* Regulation for Energy Labelling  
 2019/2020 \* Regulation for Ecodesign  
 2021/340 \* Amending Reg. Energy Labelling  
 2021/341 \* Amending Reg. Ecodesign

## Product standards

CEI EN 55015:2020 (+A11:2020)  
 CEI EN 60598-1:2022  
 CEI EN 60598-2-1:2022  
 CEI EN 61000-3-2:2019 (+A1:2021)  
 CEI EN 61000-3-3:2014 (+EC1:2014/+EC2:2016/+A1:2021/+A2:2022)  
 CEI EN 61547:2010  
 CEI EN 62031:2021 (+A11:2022)  
 CEI EN 62471:2010  
 IEC/TR 62471-2:2009  
 CEI EN 62493:2015  
 CEI 34-141:2014

## Logistics data

|                                |               |
|--------------------------------|---------------|
| Item net weight                | 1420 gr       |
| Barcode single item            | 8011905017231 |
| Number of pieces multiple pack | 10            |
| Minimum order quantity         | 10            |
| Minimum packaging              | 10 / 10       |

All parts of this document are Duralamp ownership. All rights reserved. This document and the included information are provided without any responsibility deriving from mistakes or omissions. No part of this document can be cut, reproduced or used without written authorization. Duralamp maintains the right to change the included data without notice due to improvements of the products