




## DMX 4 CHANNELS CONTROLLER FOR RGB + WHITE

### Features

Dimming and control systems can be used to improve the ambient aspect: they help creating special, different, soft and always lively atmospheres. Moreover, they have an important function of energy saving: by varying the emission and/or activating/deactivating the system or appliances, they allow optimising the presence of solar lighting. Max current 5A / channel.



### Characteristic data

Input	12-24 Vdc	Base	Screws	IP	20	LED Warranty	G5h24
-------	-----------	------	--------	----	----	--------------	-------

### Dimensional characteristics

L	168 mm
L1	51 mm
H	22 mm

### Electrical characteristics

Input voltage	12-24 Vdc
Output voltage	12-24 Vdc
Operating temperature	-25°C / +35°C

### LED Warranty

G5h24	Full Guarantee 5 years (24h/24h) Without limitations on the duration of use for the first year, provided the observance of the installation conditions.
-------	---

## European Directives

2009/125/EC \* Ecodesign  
 2011/65/EU \* RoHS  
 2012/19/EU \* RAEE  
 2014/30/EU \* EMC  
 2015/863 \* Amending RoHS  
 2017/1369 \* Regulation for Energy Labelling  
 2019/2015 \* Regulation for Energy Labelling  
 2019/2020 \* Regulation for Ecodesign  
 2021/340 \* Amending Reg. Energy Labelling  
 2021/341 \* Amending Reg. Ecodesign

## Product standards

CEI EN 55015:2020 (+A11:2020)  
 CEI EN 61000-3-2:2019 (+A1:2021)  
 CEI EN 61000-3-3:2014 (+EC1:2014/+EC2:2016/+A1:2021/+A2:2022)  
 CEI EN 61347-1:2016 (+A1:2021)  
 CEI EN 61347-2-11:2002 (+A1:2020)  
 CEI EN 61547:2010

## Logistics data

Item net weight	100 gr
Barcode single item	8011905838942
Minimum order quantity	1
Minimum packaging	1 / 1