



PING BALL

Typology

Range of LED lamps with SMD technology and color bulb.

Features

Classic shapes for immediate retro-fit of incandescent lamps in any decorative applications and festoons.

The RGB version features a fading color loop, for pleasant coloring effects.

Material

Impact-resistant globe, extremely resistant: these lamps can "bounce" if they fall on the floor.

Applications

For indoor or outdoor use inside duly protected fittings or Catenaria.

Notes

Do not use with dimmer.

BASIC

200-240
Vac



25000 h
L70B50

IP20

E27


-25°C
+35°C



Characteristic data

Power	0.5 W	Beam	320°	Dimmable	No	Input	200-240 Vac
Base	E27	IP	20	PF	0,16	LED Warranty	G2
Color	Blue						

Dimensional characteristics



Ø	45 mm
H	69 mm
H Tolerance	± 3 mm

Lighting and photometric features

Beam opening	320°
Colour of the light	Blue
Lifespan	25000 h
LED lifespan	L70B50
Trigger time	<0,2 s
Heating time up to 60% of full efficiency	Instant Full Light
Mercury	0 mg

Electrical characteristics

Rated power	0.5 W
Input voltage	200-240 Vac
Frequency	50 Hz
Dimmable	No
Power factor (PF)	0,16
Input current	0.15 A
Number of cycles	100000
Operating temperature	-25°C / +35°C
Operating position	360°

LED Warranty

G2	Up to 2 years (4000h/year) *4000h = 11h a day x 365 days. Without limitations on the duration of use for the first year, provided the observance of the installation conditions.
----	--

European Directives

2009/125/EC * Ecodesign
2011/65/EU * RoHS
2012/19/EU * RAEE
2014/30/EU * EMC
2014/35/EU * LVD
2015/863 * Amending RoHS
2017/1369 * Regulation for Energy Labelling
2019/2015 * Regulation for Energy Labelling
2019/2020 * Regulation for Ecodesign
2021/340 * Amending Reg. Energy Labelling
2021/341 * Amending Reg. Ecodesign

Product standards

CEI EN 55015:2020 (+A11:2020)
CEI EN 60968:2016
CEI EN 61000-3-2:2019 (+A1:2021)
CEI EN 61000-3-3:2014 (+EC1:2014/+EC2:2016/+A1:2021/+A2:2022)
CEI EN 61547:2010
CEI EN 62031:2021 (+A11:2022)
CEI EN 62471:2010
IEC/TR 62471-2:2009
CEI EN 62560:2013 (+A1:2017/+A11:2020)
CEI 34-141:2014

Logistics data

Item net weight	20 gr
Barcode single item	8011905836573
Number of pieces multiple pack	10
Barcode multiple pack	8011905781859
Minimum order quantity	10
Minimum packaging	10 / 10

All parts of this document are Duralamp ownership. All rights reserved. This document and the included information are provided without any responsibility deriving from mistakes or omissions. No part of this document can be cut, reproduced or used without written authorization. Duralamp maintains the right to change the included data without notice due to improvements of the products