

## PANTH ST

### Typology

LED projector "minimal design" for outdoor and indoor applications.

### Features

It can be connected to motion or twilight sensors.

Very small dimensions and design that meets the most demanding aesthetic requirements.

Supplied with an orientable mounting bracket.

### Material

Painted die-cast metal body.


### Beam

120°

### Notes

Do not use with dimmer.


Free wire for professional use (30 cm long).



### Characteristic data

Power	10 W	Beam	120°	Dimmable	No	Input	220-240 Vac
Base	Terminals	IP	65	Flux	850 lm	PF	0,90
Tc	4000 K	Ra	>80	LED Warranty	G3	Axis	340 cd
RG	RG1	Color	Black				

### Dimensional characteristics



L	103 mm
L1	26 mm
H	83 mm

## Lighting and photometric features

Beam opening	120°
Flux	850 lm
CCT nominal colour temperature	4000 K
Colour of the light	Natural light
Colour rendering index	>80
Lifespan	20000 h
LED lifespan	L70B30
Trigger time	<0,2 s
Heating time up to 60% of full efficiency	Instant Full Light

## Electrical characteristics

Rated power	10 W
Input voltage	220-240 Vac
Frequency	50-60 Hz
Dimmable	No
Power factor (PF)	0,90
Operating temperature	-25°C / +35°C


## Photometry

	4000K	H(m)	D1(m)	D2(m)	E <sub>max</sub> (lx)	
	Ra80		95°	75°		
	Fixture Power	10W	1	2.17	1.55	384
	Source Flux	750lm	2	4.35	3.09	96
	Fixture Flux	750lm	3	6.52	4.64	43
	Efficacy	75lm/W	4	8.70	6.18	24
	932299 I <sub>max</sub> =512cd/klm	I <sub>max</sub>	384cd	5	10.87	7.73

EuLumDat file on the site

## Other Infotech

Light source replaceability	Replaceable light source by a professional.
Control gear replaceability	Non-replaceable control gear.



## LED Warranty

G3	Up to 3 years (4000h/year) *4000h = 11h a day x 365 days. Without limitations on the duration of use for the first year, provided the observance of the installation conditions.
----	--

## European Directives

2009/125/EC \* Ecodesign  
2011/65/EU \* RoHS  
2012/19/EU \* RAEE  
2014/30/EU \* EMC  
2014/35/EU \* LVD  
2015/863 \* Amending RoHS  
2017/1369 \* Regulation for Energy Labelling  
2019/2015 \* Regulation for Energy Labelling  
2019/2020 \* Regulation for Ecodesign  
2021/340 \* Amending Reg. Energy Labelling  
2021/341 \* Amending Reg. Ecodesign

## Product standards

CEI EN 55015:2020 (+A11:2020)  
CEI EN 60598-1:2022  
CEI EN 60598-2-5:2016  
CEI EN 61000-3-2:2019 (+A1:2021)  
CEI EN 61000-3-3:2014 (+EC1:2014/+EC2:2016/+A1:2021/+A2:2022)  
CEI EN 61547:2010  
CEI EN 62031:2021 (+A11:2022)  
CEI EN 62471:2010  
IEC/TR 62471-2:2009  
CEI EN 62493:2015  
CEI 34-141:2014

## Logistics data

Item net weight	200 gr
Barcode single item	8011905932299
Number of pieces multiple pack	30
Barcode multiple pack	8011905932442
Minimum order quantity	5
Minimum packaging	5 / 30