



DECORATIVE SUSPENSION PROFILES: P07A

Features

Surface or suspension installation profile.

Slightly extruded rounded diffuser.

The dimensions of the profile, 5 x 6 cm, and the 180° beam opening, allows for this profile to be installed anywhere whilst responding to many needs using the same aesthetic element.

CAN BE USED WITH LED STRIPS WITH MAXIMUM WIDTH:

40 mm

MAXIMUM POWER:

40W/m

Installation

Surface or suspension installation.

The profile housing allows for some drivers to be inserted: always check dimensions and electrical loads.

Material

6063 aluminium profile with white polycarbonate screen.

Accessories

Every 3 metre bar is complete with 3 sets of end caps (with and without hole) and 3 sets of fixing brackets (necessary for surface and suspension installation) and 3 sets of suspension cables.

Packaging

Supplied in packaging of 1 bars of 3 meters complete with screen and accessories.


Spare accessories for additional cutting available with a separate code.

Notes

Thanks to the possibility of using different strips the profile becomes a fixture that can provide different light temperatures, to be used depending on the activities carried out in that space at different times during the day.

-15°C
+35°C

Dimensional characteristics



| | |
|----|---------|
| L | 3000 mm |
| L1 | 50 mm |
| H | 60 mm |

Electrical characteristics

| | |
|-----------------------|---------------|
| Operating temperature | -15°C / +35°C |
|-----------------------|---------------|

European Directives

| | |
|---|--|
| 2011/65/EU * RoHS 2015/863 * Amending RoHS | |
|---|--|

Logistics data

Barcode single item

8011905913366