



SURFACE PROFILES: PRAP

Features

Aluminium profile for surface mounting installations. Aluminium profiles allow for a more stable installation, in case of linear installations. Recommended for indoor and outdoor (protected) applications and for high power strips in order to better heat dissipation.

CAN BE USED WITH LED STRIPS WITH MAXIMUM WIDTH:

12 mm (PRAP20) and 15 mm (PRAP68).

MAXIMUM POWER:

20W/m 20 Series
25W/m 68 Series

Installation

Surface installation with its fixing clips. IP65 or IP68 strips the connectors rest outside the profile.

Material

6063 Aluminium profile with a white PC screen.


Accessories

Every 2 metre bar is complete with 1 set of end caps (with and without holes) and 1 set of mounting clips.

Packaging

Supplied in packages of 5 bars, each one measuring 2 meters complete with screen and accessories.

Dimensional characteristics



L	2000 mm
L1	16 mm
H	12 mm

European Directives

2011/65/EU * RoHS
2015/863 * Amending RoHS

Logistics data

Item net weight	440 gr
Barcode single item	8011905951405
Number of pieces multiple pack	5
Barcode multiple pack	8011905951733
Minimum order quantity	5
Minimum packaging	5 / 5

All parts of this document are Duralamp ownership. All rights reserved. This document and the included information are provided without any responsibility deriving from mistakes or omissions. No part of this document can be cut, reproduced or used without written authorization. Duralamp maintains the right to change the included data without notice due to improvements of the products