



## DALI CONTROLLER FOR DURAstrip

### Features

Dimming and control systems can be used to improve the ambient aspect: they help creating special, different, soft and always lively atmospheres. Moreover, they have an important function of energy saving: by varying the emission and/or activating/deactivating the system or appliances, they allow optimising the presence of solar lighting. Max current 8A / channel.

PRO

12-24 Vdc

IP20

Screws

-25°C  
+35°C

III


FLICKER  
FREE

G5  
h24

### Characteristic data

Input	12-24 Vdc	Base	Screws	IP	20	LED Warranty	G5h24
-------	-----------	------	--------	----	----	--------------	-------

### Dimensional characteristics



L	167 mm
L1	51 mm
L2	51 mm
H	23 mm

### Electrical characteristics

Input voltage	12-24 Vdc
Output voltage	12-24 Vdc
Operating temperature	-25°C / +35°C

## Other Infotech

Flicker Free	Yes
--------------	-----

## LED Warranty

G5h24	Full Guarantee 5 years (24h/24h) Without limitations on the duration of use for the first year, provided the observance of the installation conditions.
-------	---

## European Directives

2009/125/EC \* Ecodesign  
2011/65/EU \* RoHS  
2012/19/EU \* RAEE  
2014/30/EU \* EMC  
2015/863 \* Amending RoHS  
2017/1369 \* Regulation for Energy Labelling  
2019/2015 \* Regulation for Energy Labelling  
2019/2020 \* Regulation for Ecodesign  
2021/340 \* Amending Reg. Energy Labelling  
2021/341 \* Amending Reg. Ecodesign

## Product standards

CEI EN 55015:2020 (+A11:2020)  
CEI EN 61000-3-2:2019 (+A1:2021)  
CEI EN 61000-3-3:2014 (+EC1:2014/+EC2:2016/+A1:2021/+A2:2022)  
CEI EN 61347-1:2016 (+A1:2021)  
CEI EN 61347-2-11:2002 (+A1:2020)  
CEI EN 61547:2010

## Logistics data

Item net weight	100 gr
Barcode single item	8011905955410
Minimum order quantity	1
Minimum packaging	1 / 1