



PROJECTOR JAZZ03

Typology

LED projector with COB technology for outdoor spot lighting.

Features

Sleek design that can be used in any setting; adjustable to 240°. Projector with base with integrated driver.

Material

Anthracite grey colour, powder coated anodised aluminium body.

Beam

LED Chip on Board, high efficiency, Ra 85.
Adjustable from 0° to 240° on the vertical axis and 350° on the horizontal axis.



220-240
Vac

Ra >85




50000 h
L70B20

IP65

Wire

-25°C
+35°C




40°



Characteristic data

Power	30 W	Beam	40°	Dimmable	Yes	Input	220-240 Vac
Base	Wire	IP	65	Flux	3000 lm	PF	0,9
Tc	4000 K	Ra	>85	LED Warranty	G5h24	Axis	4100 cd
Color	Anthracite						

Dimensional characteristics



Ø	100 mm
L2	95 mm
H	210 mm

Lighting and photometric features

Beam opening	40°
Flux	3000 lm
CCT nominal colour temperature	4000 K
Colour of the light	Natural light
Colour rendering index	>85
Lifespan	50000 h
LED lifespan	L70B20
Trigger time	<0,2 s
Heating time up to 60% of full efficiency	Instant Full Light

Electrical characteristics

Rated power	30 W
Input voltage	220-240 Vac
Frequency	50-60 Hz
Dimmable	Yes
Power factor (PF)	0,9
Input current	0.14 A
Weighted energy consumption	30 kWh/1000h
Number of cycles	100000
Operating temperature	-25°C / +35°C

Photometry

	4000K	H(m)	D(m)	E _{max} (lx)		
	Ra80		57°			
	Fixture Power	30W	1	1.10	4157	
	Source Flux	3500lm	2	2.19	1039	
	Fixture Flux	3500lm	3	3.29	462	
	Efficacy	117lm/W	4	4.39	260	
	862442	Imax=1188cd/klm	Imax	4157cd	5	5.48

EuLumDat file on the site

LED Warranty

G5h24	<p>Full Guarantee</p> <p>5 years</p> <p>(24h/24h) Without limitations on the duration of use for the first year, provided the observance of the installation conditions.</p>
-------	--

European Directives

2009/125/EC * Ecodesign
 2011/65/EU * RoHS
 2012/19/EU * RAEE
 2014/30/EU * EMC
 2014/35/EU * LVD
 2015/863 * Amending RoHS
 2017/1369 * Regulation for Energy Labelling
 2019/2015 * Regulation for Energy Labelling
 2019/2020 * Regulation for Ecodesign
 2021/340 * Amending Reg. Energy Labelling
 2021/341 * Amending Reg. Ecodesign

Product standards

CEI EN 55015:2020 (+A11:2020)
 CEI EN 60598-1:2022
 CEI EN 60598-2-1:2022
 CEI EN 61000-3-2:2019 (+A1:2021)
 CEI EN 61000-3-3:2014 (+EC1:2014/+EC2:2016/+A1:2021/+A2:2022)
 CEI EN 61547:2010
 CEI EN 62031:2021 (+A11:2022)
 CEI EN 62471:2010
 IEC/TR 62471-2:2009
 CEI EN 62493:2015
 CEI 34-141:2014

Logistics data

Item net weight	1700 gr
Barcode single item	8011905862442
Minimum order quantity	1

All parts of this document are Duralamp ownership. All rights reserved. This document and the included information are provided without any responsibility deriving from mistakes or omissions. No part of this document can be cut, reproduced or used without written authorization. Duralamp maintains the right to change the included data without notice due to improvements of the products