



## STAGNA S2T L1 IP65 - 25000H

### Typology

Waterproof linear ceiling light with G13 connection for 2 TUBOLED.  
Complete with 25,000h Tuboled.

### Features

Quick opening mechanism for wiring.  
Designed to withstand dust and water jets.

### Installation

"Snap on" AISI 316 stainless steel brackets for ceiling or suspension installation.  
Every batten is equipped with brackets.

### Material

Polycarbonate body and transparent polycarbonate screen.

### Applications

Supermarkets, car parks, laboratories, warehouses.



### Characteristic data

Power	36 W	Dimmable	No	Input	220-240 Vac	Base	G13
IP	65	Flux	3650 lm	PF	0,7	Tc	6000 K
Ra	>80	LED Warranty	G2	IK	IK07	RG	RG0

### Dimensional characteristics



L	1275 mm
L1	95 mm
H	60 mm

## Lighting and photometric features

Flux	3650 lm
CCT nominal colour temperature	6000 K
Colour rendering index	>80
Lifespan	25000 h
LED lifespan	L70B50

## Electrical characteristics

Rated power	36 W
Input voltage	220-240 Vac
Frequency	50-60 Hz
Dimmable	No
Power factor (PF)	0,7
Operating temperature	-25°C / +35°C

## Photometry

EuLumDat file on the site

## LED Warranty

G2	Up to 2 years (4000h/year) *4000h = 11h a day x 365 days. Without limitations on the duration of use for the first year, provided the observance of the installation conditions.
----	--

## European Directives

2009/125/EC \* Ecodesign  
2011/65/EU \* RoHS  
2012/19/EU \* RAEE  
2014/30/EU \* EMC  
2014/35/EU \* LVD  
2015/863 \* Amending RoHS  
2017/1369 \* Regulation for Energy Labelling  
2019/2015 \* Regulation for Energy Labelling  
2019/2020 \* Regulation for Ecodesign  
2021/340 \* Amending Reg. Energy Labelling  
2021/341 \* Amending Reg. Ecodesign

## Product standards

CEI EN 55015:2020 (+A11:2020)  
CEI EN 60598-1:2022  
CEI EN 60598-2-1:2022  
CEI EN 61000-3-2:2019 (+A1:2021)  
CEI EN 61000-3-3:2014 (+EC1:2014/+EC2:2016/+A1:2021/+A2:2022)  
CEI EN 61547:2010  
CEI EN 62031:2021 (+A11:2022)  
CEI EN 62471:2010  
IEC/TR 62471-2:2009  
CEI EN 62493:2015  
CEI 34-141:2014

## Logistics data

Item net weight	830 gr
Barcode single item	8011905017309
Number of pieces multiple pack	10
Minimum order quantity	10
Minimum packaging	10 / 10

All parts of this document are Duralamp ownership. All rights reserved. This document and the included information are provided without any responsibility deriving from mistakes or omissions. No part of this document can be cut, reproduced or used without written authorization. Duralamp maintains the right to change the included data without notice due to improvements of the products