



## MARAMA

### Typology

LED table lamp, dimmable and cordless.  
Elegant and essential design, perfect for both modern and classical settings.  
Diffused light directed downwards.

### Features

Warm white dimmable version.  
Marama is operated by a touch on the top of the diffuser: the touch activates on/off and light intensity.

### Material







Powder-coated aluminium; frosted polycarbonate screen.

### Usage information

Battery: battery life of up to 12 hours at full light output and up to 5 days at the lowest output.  
Equipped with large capacity 6600mAh rechargeable lithium battery.  
Battery charging time: 5~6 hours.

### Accessories

Type-C charging cable supplied (can be used with any cable with Type-C jack; USB C charger not included).  
USB Multicharger 8 port charge also available to charge 8 lamps simultaneously.



### Characteristic data

Power	2 W	Dimmable	Yes	Input	5 Vdc	IP	53
Flux	100 lm	Tc	3000 K	Ra	90	LED Warranty	G3
RG	RG0	Color	Black				

## Dimensional characteristics



Ø	100 mm
Ø1	120 mm
H	350 mm

## Lighting and photometric features

Flux	100 lm
CCT nominal colour temperature	3000 K
Colour of the light	Warm light
Colour rendering index	90
Lifespan	50000 h
LED lifespan	L70B20
Trigger time	<0,2 s
Heating time up to 60% of full efficiency	Instant Full Light

## Electrical characteristics

Rated power	2 W
Input voltage	5 Vdc
Dimmable	Yes
Input current	2 A
Operating temperature	-25°C / +45°C

## Photometry

EuLumDat file on the site

## LED Warranty

G3	Up to 3 years (4000h/year) *4000h = 11h a day x 365 days. Without limitations on the duration of use for the first year, provided the observance of the installation conditions.
----	--

## European Directives

2009/125/EC \* Ecodesign  
 2011/65/EU \* RoHS  
 2012/19/EU \* RAEE  
 2014/30/EU \* EMC  
 2014/35/EU \* LVD  
 2015/863 \* Amending RoHS  
 2017/1369 \* Regulation for Energy Labelling  
 2019/2015 \* Regulation for Energy Labelling  
 2019/2020 \* Regulation for Ecodesign  
 2021/340 \* Amending Reg. Energy Labelling  
 2021/341 \* Amending Reg. Ecodesign

## Product standards

CEI EN 55015:2020 (+A11:2020)  
 CEI EN 60598-1:2022  
 CEI EN 60598-2-4:2019  
 CEI EN 61000-3-2:2019 (+A1:2021)  
 CEI EN 61000-3-3:2014 (+EC1:2014/+EC2:2016/+A1:2021/+A2:2022)  
 CEI EN 61547:2010  
 CEI EN 62031:2021 (+A11:2022)  
 CEI EN 62471:2010  
 IEC/TR 62471-2:2009  
 CEI EN 62493:2015  
 CEI 34-141:2014

## Logistics data

Item net weight	850 gr
Barcode single item	8011905988111
Number of pieces multiple pack	10
Barcode multiple pack	8011905988401
Minimum order quantity	1
Minimum packaging	1 / 10