



DECO LED TECNO VINTAGE TRANSPARENT GLS

Typology

Range of lamps "filament LED": micro-led sources - that optimise thermal management - are positioned on a glass support and completely covered with phosphor powder that unifies, amplifies and diffuses the light.

Features

Excellent colour maintenance and are light constant over time. The spectrum of Tecno Vintage lamps is particularly rich in the warm colour bands to obtain an effect as close as possible to that of the lamps to be replaced.

Material

Glass bulb.

Notes

Do not use with dimmers except if otherwise indicated.



Characteristic data

Power	10 W	Beam	320°	Dimmable	No	Input	220-240 Vac
Base	E27	IP	20	Flux	1521 lm	PF	0,50
Tc	2700 K	Ra	80	LED Warranty	G2		

Dimensional characteristics

ø	60 mm
H	105 mm

Lighting and photometric features

Beam opening	320°
Flux	1521 lm
CCT nominal colour temperature	2700 K
Colour of the light	Warm light
Colour rendering index	80
Lifespan	15000 h
LED lifespan	L70B50
Trigger time	<0,2 s
Heating time up to 60% of full efficiency	Instant Full Light
Mercury	0 mg

Electrical characteristics

Rated power	10 W
Input voltage	220-240 Vac
Frequency	50 Hz
Dimmable	No
Power factor (PF)	0,50
Weighted energy consumption	10 kWh/1000h
Energy efficiency class	D
Operating temperature	-25°C / +35°C
Equivalence with incandescent lamp	100
Operating position	360°

LED Warranty

G2	Up to 2 years (4000h/year) * 4000h = 11h a day x 365 days. Without limitations on the duration of use for the first year, provided the observance of the installation conditions.
----	---

European Directives

2009/125/EC * Ecodesign
2011/65/EU * RoHS
2012/19/EU * RAEE
2014/30/EU * EMC
2014/35/EU * LVD
2015/863 * Amending RoHS
2017/1369 * Regulation for Energy Labelling
2019/2015 * Regulation for Energy Labelling
2019/2020 * Regulation for Ecodesign
2021/340 * Amending Reg. Energy Labelling
2021/341 * Amending Reg. Ecodesign

Product standards

CEI EN 55015:2020 (+A11:2020)
CEI EN 60968:2016
CEI EN 61000-3-2:2019 (+A1:2021)
CEI EN 61000-3-3:2014 (+EC1:2014/+EC2:2016/+A1:2021/+A2:2022)
CEI EN 61547:2010
CEI EN 62031:2021 (+A11:2022)
CEI EN 62471:2010
IEC/TR 62471-2:2009
CEI EN 62560:2013 (+A1:2017/+A11:2020)
CEI 34-141:2014

Logistics data

Item net weight	33 gr
Barcode single item	8011905325541
Number of pieces multiple pack	10
Minimum order quantity	10
Minimum packaging	10 / 10