



MARAMA

Typology

LED table lamp, dimmable and cordless.
Elegant and essential design, perfect for both modern and classical settings.
Diffused light directed downwards.

Features

Warm white dimmable version.
Marama is operated by a touch on the top of the diffuser: the touch activates on/off and light intensity.

Material



Powder-coated aluminium; frosted polycarbonate screen.

Usage information

Battery: battery life of up to 12 hours at full light output and up to 5 days at the lowest output.
Equipped with large capacity 6600mAh rechargeable lithium battery.
Battery charging time: 5~6 hours.

Accessories

Type-C charging cable supplied (can be used with any cable with Type-C jack; USB C charger not included).
USB Multicharger 8 port charge also available to charge 8 lamps simultaneously.



Characteristic data

Power	2 W	Dimmable	Yes	Input	5 Vdc	IP	53
Flux	100 lm	Tc	3000 K	Ra	90	LED Warranty	G3
RG	RG0	Color	White				

Dimensional characteristics



Ø	100 mm
Ø1	120 mm
H	350 mm

Lighting and photometric features

Flux	100 lm
CCT nominal colour temperature	3000 K
Colour of the light	Warm light
Colour rendering index	90
Lifespan	50000 h
LED lifespan	L70B20
Trigger time	<0,2 s
Heating time up to 60% of full efficiency	Instant Full Light

Electrical characteristics

Rated power	2 W
Input voltage	5 Vdc
Dimmable	Yes
Input current	2 A
Operating temperature	-25°C / +45°C

Photometry

EuLumDat file on the site

LED Warranty

G3	Up to 3 years (4000h/year) *4000h = 11h a day x 365 days. Without limitations on the duration of use for the first year, provided the observance of the installation conditions.
----	--

European Directives

2009/125/EC * Ecodesign
 2011/65/EU * RoHS
 2012/19/EU * RAEE
 2014/30/EU * EMC
 2014/35/EU * LVD
 2015/863 * Amending RoHS
 2017/1369 * Regulation for Energy Labelling
 2019/2015 * Regulation for Energy Labelling
 2019/2020 * Regulation for Ecodesign
 2021/340 * Amending Reg. Energy Labelling
 2021/341 * Amending Reg. Ecodesign

Product standards

CEI EN 55015:2020 (+A11:2020)
 CEI EN 60598-1:2022
 CEI EN 60598-2-4:2019
 CEI EN 61000-3-2:2019 (+A1:2021)
 CEI EN 61000-3-3:2014 (+EC1:2014/+EC2:2016/+A1:2021/+A2:2022)
 CEI EN 61547:2010
 CEI EN 62031:2021 (+A11:2022)
 CEI EN 62471:2010
 IEC/TR 62471-2:2009
 CEI EN 62493:2015
 CEI 34-141:2014

Logistics data

Item net weight	850 gr
Barcode single item	8011905988111
Number of pieces multiple pack	10
Barcode multiple pack	8011905988401
Minimum order quantity	1
Minimum packaging	1 / 10