



DR111 - WF 230V

Typology

LED DR111.

Features

Reflector Effect: coverage of the light source makes these lamps similar to traditional halogen sources they are intended to replace.

Material

High reflectance metal reflector.

Base in thermoresistant plastic material.

Lightness is an important feature of this product: ideal for use on any type of ceiling or fitting.

Applications

Professional directional lighting: ideal for use in shops and in areas where accent lighting is required.



220-240
Vac

Ra 80




25000 h
L70B50

IP20

GU10


-25°C
+35°C



Characteristic data

Power	11 W	Beam	30°	Dimmable	Yes	Input	220-240 Vac
Base	GU10	IP	20	Flux	1100 lm	Axis	1700 cd
PF	0,50	Tc	3000 K	Ra	80	LED Warranty	G2

Dimensional characteristics



Ø	111 mm
H	72 mm

Lighting and photometric features

Beam opening	30°
Flux	1100 lm
Axis	1700 cd
CCT nominal colour temperature	3000 K
Colour of the light	Warm light
Colour rendering index	80
Lifespan	25000 h
LED lifespan	L70B50
Trigger time	<0,2 s
Heating time up to 60% of full efficiency	Instant Full Light
Mercury	0 mg

Electrical characteristics

Rated power	11 W
Input voltage	220-240 Vac
Frequency	50/60 Hz
Dimmable	Yes
Power factor (PF)	0,50
Weighted energy consumption	11 kWh/1000h
Energy efficiency class	F
Operating temperature	-25°C / +35°C
Equivalence with incandescent lamp	92
Operating position	360°

LED Warranty

G2	Up to 2 years (4000h/year) *4000h = 11h a day x 365 days. Without limitations on the duration of use for the first year, provided the observance of the installation conditions.
----	--

European Directives

2009/125/EC * Ecodesign
2011/65/EU * RoHS
2012/19/EU * RAEE
2014/30/EU * EMC
2014/35/EU * LVD
2015/863 * Amending RoHS
2017/1369 * Regulation for Energy Labelling
2019/2015 * Regulation for Energy Labelling
2019/2020 * Regulation for Ecodesign
2021/340 * Amending Reg. Energy Labelling
2021/341 * Amending Reg. Ecodesign

Product standards

CEI EN 55015:2020 (+A11:2020)
CEI EN 60968:2016
CEI EN 61000-3-2:2019 (+A1:2021)
CEI EN 61000-3-3:2014 (+EC1:2014/+EC2:2016/+A1:2021/+A2:2022)
CEI EN 61547:2010
CEI EN 62031:2021 (+A11:2022)
CEI EN 62471:2010
IEC/TR 62471-2:2009
CEI EN 62560:2013 (+A1:2017/+A11:2020)
CEI 34-141:2014

Logistics data

Item net weight	118 gr
Barcode single item	8011905850159
Number of pieces multiple pack	5
Barcode multiple pack	8011905851149
Minimum order quantity	5
Minimum packaging	5 / 5

All parts of this document are Duralamp ownership. All rights reserved. This document and the included information are provided without any responsibility deriving from mistakes or omissions. No part of this document can be cut, reproduced or used without written authorization. Duralamp maintains the right to change the included data without notice due to improvements of the products