



LED ROUND TRIPACK

Typology

LED lamps in convenient 3-piece packs.

Features

The same quality as other lamps, optimised packaging.

220-240
Vac

Ra >80



IP20

E27


240°



Characteristic data

Power	5.7 W	Beam	240°	Dimmable	No	Input	220-240 Vac
Base	E27	IP	20	Flux	500 lm	PF	0,5
Tc	6000 K	Ra	>80	LED Warranty	G2		

Dimensional characteristics



Ø	45 mm
H	77 mm
H Tolerance	± 3 mm

Lighting and photometric features

Beam opening	240°
Flux	500 lm
CCT nominal colour temperature	6000 K
Colour of the light	Cool light
Colour rendering index	>80
LED lifespan	L70B50
Heating time up to 60% of full efficiency	Instant Full Light
Mercury	0 mg

Electrical characteristics

Rated power	5.7 W
Input voltage	220-240 Vac
Frequency	50 Hz
Dimmable	No
Power factor (PF)	0,5
Input current	0.05 A
Weighted energy consumption	6 kWh/1000h
Number of cycles	100000
Equivalence with incandescent lamp	42

LED Warranty

G2	Up to 2 years (4000h/year) *4000h = 11h a day x 365 days. Without limitations on the duration of use for the first year, provided the observance of the installation conditions.
----	--

European Directives

2009/125/EC * Ecodesign
2011/65/EU * RoHS
2012/19/EU * RAEE
2014/30/EU * EMC
2014/35/EU * LVD
2015/863 * Amending RoHS
2017/1369 * Regulation for Energy Labelling
2019/2015 * Regulation for Energy Labelling
2019/2020 * Regulation for Ecodesign
2021/340 * Amending Reg. Energy Labelling
2021/341 * Amending Reg. Ecodesign

Product standards

CEI EN 55015:2020 (+A11:2020)
CEI EN 60968:2016
CEI EN 61000-3-2:2019 (+A1:2021)
CEI EN 61000-3-3:2014 (+EC1:2014/+EC2:2016/+A1:2021/+A2:2022)
CEI EN 61547:2010
CEI EN 62031:2021 (+A11:2022)
CEI EN 62471:2010
IEC/TR 62471-2:2009
CEI EN 62560:2013 (+A1:2017/+A11:2020)
CEI 34-141:2014

Logistics data

Item net weight	100 gr
Barcode single item	8011905852931
Number of pieces multiple pack	6
Barcode multiple pack	8011905852948