



VALO CCT ROUND

Typology

Compact adjustable LED downlight with integrated driver and colour temperature selection function.

Features


Compact and easy to install.
Tilt Adjustability 30°.

Installation

Complete with springs for easy fastening into false ceilings.

Material


Heat resistant, anti-yellowing plastic body.



Characteristic data

Power	7 W	Beam	50°	Dimmable	No	Input	220-240 Vac
Base	Free Wire	IP	20	Optical compartment IP	43	Flux	600 lm
Axis	570 cd	PF	0,5	Tc	3000-4000-6500 K	Ra	>80
LED Warranty	G2	RG	RG1				

Dimensional characteristics



Ø	85 mm
H	39 mm

Cutting hole	70
--------------	----

Lighting and photometric features

Beam opening	50°
Flux	600 lm
Axis	570 cd
CCT nominal colour temperature	3000-4000-6500 K
Colour of the light	CCT
Colour rendering index	>80
Lifespan	15000 h
LED lifespan	L70B20
Heating time up to 60% of full efficiency	Instant Full Light

Electrical characteristics

Rated power	7 W
Input voltage	220-240 Vac
Frequency	50/60 Hz
Dimmable	No
Power factor (PF)	0,5
Input current	0.02 A
Weighted energy consumption	7 kWh/1000h
Operating temperature	-25°C / +35°C

LED Warranty

G2	Up to 2 years (4000h/year) *4000h = 11h a day x 365 days. Without limitations on the duration of use for the first year, provided the observance of the installation conditions.
----	--

European Directives

2009/125/EC * Ecodesign
2011/65/EU * RoHS
2012/19/EU * RAEE
2014/30/EU * EMC
2014/35/EU * LVD
2015/863 * Amending RoHS
2017/1369 * Regulation for Energy Labelling
2019/2015 * Regulation for Energy Labelling
2019/2020 * Regulation for Ecodesign
2021/340 * Amending Reg. Energy Labelling
2021/341 * Amending Reg. Ecodesign

Product standards

CEI EN 55015:2020 (+A11:2020)
CEI EN 60598-1:2022
CEI EN 60598-2-2:2012
CEI EN 61000-3-2:2019 (+A1:2021)
CEI EN 61000-3-3:2014 (+EC1:2014/+EC2:2016/+A1:2021/+A2:2022)
CEI EN 61547:2010
CEI EN 62031:2021 (+A11:2022)
CEI EN 62471:2010
IEC/TR 62471-2:2009
CEI EN 62493:2015
CEI 34-141:2014

Logistics data

Item net weight	16 gr
Barcode single item	8011905331696
Number of pieces multiple pack	10
Minimum order quantity	10
Minimum packaging	10 / 10

All parts of this document are Duralamp ownership. All rights reserved. This document and the included information are provided without any responsibility deriving from mistakes or omissions. No part of this document can be cut, reproduced or used without written authorization. Duralamp maintains the right to change the included data without notice due to improvements of the products