



## PING BALL

### Typology

Range of LED lamps with SMD technology and color bulb.

### Features

Classic shapes for immediate retro-fit of incandescent lamps in any decorative applications and festoons.

The RGB version features a fading color loop, for pleasant coloring effects.

### Material

Impact-resistant globe, extremely resistant: these lamps can "bounce" if they fall on the floor.

### Applications

For indoor or outdoor use inside duly protected fittings or Catenaria.

### Notes

Do not use with dimmer.

**BASIC**

200-240  
Vac



25000 h  
L70B50

IP20

B22

-25°C  
+35°C




320°



### Characteristic data

Power	0.5 W	Beam	320°	Dimmable	No	Input	200-240 Vac
Base	B22	IP	20	LED Warranty	G2	Color	Green

### Dimensional characteristics



Ø	45 mm
H	69 mm
H Tolerance	± 3 mm

## Lighting and photometric features

Beam opening	320°
Colour of the light	Green
Lifespan	25000 h
LED lifespan	L70B50
Trigger time	<0,2 s
Heating time up to 60% of full efficiency	Instant Full Light
Mercury	0 mg

## Electrical characteristics

Rated power	0.5 W
Input voltage	200-240 Vac
Frequency	50 Hz
Dimmable	No
Input current	0.15 A
Number of cycles	100000
Operating temperature	-25°C / +35°C
Operating position	360°

## LED Warranty

G2	Up to 2 years (4000h/year) *4000h = 11h a day x 365 days. Without limitations on the duration of use for the first year, provided the observance of the installation conditions.
----	--

## European Directives

2009/125/EC \* Ecodesign  
2011/65/EU \* RoHS  
2012/19/EU \* RAEE  
2014/30/EU \* EMC  
2014/35/EU \* LVD  
2015/863 \* Amending RoHS  
2017/1369 \* Regulation for Energy Labelling  
2019/2015 \* Regulation for Energy Labelling  
2019/2020 \* Regulation for Ecodesign  
2021/340 \* Amending Reg. Energy Labelling  
2021/341 \* Amending Reg. Ecodesign

## Product standards

CEI EN 55015:2020 (+A11:2020)  
CEI EN 60968:2016  
CEI EN 61000-3-2:2019 (+A1:2021)  
CEI EN 61000-3-3:2014 (+EC1:2014/+EC2:2016/+A1:2021/+A2:2022)  
CEI EN 61547:2010  
CEI EN 62031:2021 (+A11:2022)  
CEI EN 62471:2010  
IEC/TR 62471-2:2009  
CEI EN 62560:2013 (+A1:2017/+A11:2020)  
CEI 34-141:2014

## Logistics data

Item net weight	20 gr
Barcode single item	8011905836740
Number of pieces multiple pack	10
Barcode multiple pack	8011905782023
Minimum order quantity	10
Minimum packaging	10 / 10