



LED DRIVER

Features

Driver for LED strips.
SELV equivalent; protection device in case of short circuit or overload in the secondary circuit.
24V drivers have loose wires connection and are TUV marked.
60W and 100W SL drivers are fit for use inside aluminium profiles where indicated.



Characteristic data

Power	80 W	Dimmable	No	Input	110-260 Vac	IP	20
PF	0,9	LED Warranty	G5h24				

Dimensional characteristics

L	320 mm
L1	30 mm
H	17 mm

Lighting and photometric features

Lifespan	50000 h
----------	---------

Electrical characteristics

Rated power	80 W
Input voltage	110-260 Vac
Frequency	50 Hz
Output voltage	24 Vdc
Dimmable	No
Power factor (PF)	0,9
Input current	6.6 A
Operating temperature	-20°C / +45°C

Other Infotech

Flicker Free	Yes
Max Case Temperature	80

LED Warranty

G5h24	Full Guarantee 5 years (24h/24h) Without limitations on the duration of use for the first year, provided the observance of the installation conditions.
-------	---

European Directives

2009/125/EC * Ecodesign
2011/65/EU * RoHS
2012/19/EU * RAEE
2014/30/EU * EMC
2014/35/EU * LVD
2015/863 * Amending RoHS
2017/1369 * Regulation for Energy Labelling
2019/2015 * Regulation for Energy Labelling
2019/2020 * Regulation for Ecodesign
2021/340 * Amending Reg. Energy Labelling
2021/341 * Amending Reg. Ecodesign

Product standards

CEI EN 55015:2020 (+A11:2020)
CEI EN 61000-3-2:2019 (+A1:2021)
CEI EN 61000-3-3:2014 (+EC1:2014/+EC2:2016/+A1:2021/+A2:2022)
CEI EN 61347-1:2016 (+A1:2021)
CEI EN 61347-2-13:2015 (+A1:2018)
CEI EN 61547:2010

Logistics data

Item net weight	206 gr
Barcode single item	8011905976422
Minimum order quantity	1
Minimum packaging	1 / 1