




DMX 3 CHANNELS CONTROLLER FOR RGB

Features


Dimming and control systems can be used to improve the ambient aspect: they help creating special, different, soft and always lively atmospheres. Moreover, they have an important function of energy saving: by varying the emission and/or activating/deactivating the system or appliances, they allow optimising the presence of solar lighting. Max current 5A / channel.



Characteristic data

Input	12-24 Vdc	Base	Screws	IP	20	LED Warranty	G5h24
-------	-----------	------	--------	----	----	--------------	-------

Dimensional characteristics



L	178 mm
L1	42 mm
H	33 mm

Electrical characteristics

Input voltage	12-24 Vdc
Output voltage	12-24 Vdc
Operating temperature	-25°C / +35°C

LED Warranty

G5h24	Full Guarantee 5 years (24h/24h) Without limitations on the duration of use for the first year, provided the observance of the installation conditions.
-------	---

European Directives

2009/125/EC * Ecodesign
2011/65/EU * RoHS
2012/19/EU * RAEE
2014/30/EU * EMC
2015/863 * Amending RoHS
2017/1369 * Regulation for Energy Labelling
2019/2015 * Regulation for Energy Labelling
2019/2020 * Regulation for Ecodesign
2021/340 * Amending Reg. Energy Labelling
2021/341 * Amending Reg. Ecodesign

Product standards

CEI EN 55015:2020 (+A11:2020)
CEI EN 61000-3-2:2019 (+A1:2021)
CEI EN 61000-3-3:2014 (+EC1:2014/+EC2:2016/+A1:2021/+A2:2022)
CEI EN 61347-1:2016 (+A1:2021)
CEI EN 61347-2-11:2002 (+A1:2020)
CEI EN 61547:2010

Logistics data

Item net weight	300 gr
Barcode single item	8011905836795
Minimum order quantity	1
Minimum packaging	1 / 1