



MR16 VINTAGE

Typology

MR16 and PAR16: same material and shape of halogen lamps.

Features

High efficiency last generation sources.

Material

Glass body.

Usage information

Compatible with 12V AC output electromagnetic transformers and with drivers for LEDs with constant current drivers.

Do not use this item with electronic transformers for halogen lamps.

Notes

Do not use with dimmer.

BASIC

12 Vdc

Ra 80



15000 h
L70B50

IP20

GU5,3


-25°C
+35°C



Characteristic data

Power	3.5 W	Beam	38°	Dimmable	No	Input	12 Vdc
Base	GU5,3	IP	20	Flux	460 lm	PF	0,71
Tc	3000 K	Ra	80	LED Warranty	G2	Axis	600 cd

Dimensional characteristics



Ø	51 mm
H	46 mm

Lighting and photometric features

Beam opening	38°
Flux	460 lm
CCT nominal colour temperature	3000 K
Colour of the light	Warm light
Colour rendering index	80
Lifespan	15000 h
LED lifespan	L70B50
Trigger time	<0,2 s
Heating time up to 60% of full efficiency	Instant Full Light
Mercury	0 mg

Electrical characteristics

Rated power	3.5 W
Input voltage	12 Vdc
Dimmable	No
Power factor (PF)	0,71
Input current	0.57 A
Weighted energy consumption	4 kWh/1000h
Energy efficiency class	E
Operating temperature	-25°C / +35°C
Equivalence with incandescent lamp	37

Other Infotech

Reflector	Yes
-----------	-----

LED Warranty

G2	Up to 2 years (4000h/year) *4000h = 11h a day x 365 days. Without limitations on the duration of use for the first year, provided the observance of the installation conditions.
----	--

European Directives

2009/125/EC * Ecodesign
2011/65/EU * RoHS
2012/19/EU * RAEE
2014/30/EU * EMC
2015/863 * Amending RoHS
2017/1369 * Regulation for Energy Labelling
2019/2015 * Regulation for Energy Labelling
2019/2020 * Regulation for Ecodesign
2021/340 * Amending Reg. Energy Labelling
2021/341 * Amending Reg. Ecodesign

Product standards

CEI EN 55015:2020 (+A11:2020)
CEI EN 62838:2016 (+EC:2018)
CEI EN 61000-3-2:2019 (+A1:2021)
CEI EN 61000-3-3:2014 (+EC1:2014/+EC2:2016/+A1:2021/+A2:2022)
CEI EN 61547:2010
CEI EN 62031:2021 (+A11:2022)
CEI EN 62471:2010
IEC/TR 62471-2:2009
CEI 34-141:2014

Logistics data

Item net weight	60 gr
Barcode single item	8011905849375
Number of pieces multiple pack	10
Barcode multiple pack	8011905849382
Minimum order quantity	10
Minimum packaging	10 / 10

All parts of this document are Duralamp ownership. All rights reserved. This document and the included information are provided without any responsibility deriving from mistakes or omissions. No part of this document can be cut, reproduced or used without written authorization. Duralamp maintains the right to change the included data without notice due to improvements of the products