



## DMX DIMMER TOUCH FOR RGB + WHITE

### Typology

Dimmers for DURASTRIP white, for DURASTRIP CTC, DURASTRIP RGB and RGB+white.

### Features

External interface in tempered glass with high touch sensibility, immediate response to touch and control precision.




4 zones can be controlled separately or synchronised.

Can be used with ZKCDMX, ZKCDMX-R, ZKCDMXW.

Conforms with protocol DMX512 (1990).

Dimmer's driver included in the box (220-240Vac / 5Vdc).


Easy installation and intuitive use.



### Characteristic data

Input	5 Vdc	Base	Screws	LED Warranty	G5h24	Color	White
-------	-------	------	--------	--------------	-------	-------	-------

### Dimensional characteristics



L	146 mm
L1	106 mm
H	10 mm

### Electrical characteristics

Input voltage	5 Vdc
Frequency	50 Hz
Operating temperature	-25°C / +35°C

## LED Warranty

G5h24	Full Guarantee 5 years (24h/24h) Without limitations on the duration of use for the first year, provided the observance of the installation conditions.
-------	---

## European Directives

2009/125/EC \* Ecodesign  
2011/65/EU \* RoHS  
2012/19/EU \* RAEE  
2014/30/EU \* EMC  
2015/863 \* Amending RoHS  
2017/1369 \* Regulation for Energy Labelling  
2019/2015 \* Regulation for Energy Labelling  
2019/2020 \* Regulation for Ecodesign  
2021/340 \* Amending Reg. Energy Labelling  
2021/341 \* Amending Reg. Ecodesign

## Product standards

CEI EN 55015:2020 (+A11:2020)  
CEI EN 61000-3-2:2019 (+A1:2021)  
CEI EN 61000-3-3:2014 (+EC1:2014/+EC2:2016/+A1:2021/+A2:2022)  
CEI EN 61347-1:2016 (+A1:2021)  
CEI EN 61347-2-11:2002 (+A1:2020)  
CEI EN 61547:2010

## Logistics data

Item net weight	310 gr
Barcode single item	8011905839659
Minimum order quantity	1
Minimum packaging	1 / 1