



PANTH H2 CCT

Typology

Super-compact professional projectors for large commercial and industrial spaces; uses highly efficient SMD technology, up to 160lm/W.
Very versatile thanks to the colour temperature selector switch: 3000K-5000K.

Features

Ultra-flat, highly efficient, long service life: reliable products for use in all areas where powerful light output with significant energy savings is required.
Equipped with voltage surge protection, see details.

Installation

Free-standing or fixed to the surface with its swivelling bracket.
Available as accessories: reinforced bracket with tilt control and bracket for mounting on pole head or wall arm (diam. 60).

Material

Die-cast aluminium body.
Suitable for use in dusty and humid environments due to IP65 rating.

Emergency

EL compatible: driver suitable for use in emergency systems with centralised backup power.

Beam


Asymmetrical beam angle: 110°.



Characteristic data

Power	150 W	Beam	55°x65°	Dimmable	No	Input	220-240 Vac
IP	66	Flux	21000 lm	PF	0.9	Tc	3000-5700 K
Ra	80	LED Warranty	G5h24	Axis	14600 cd	IK	IK08
Color	Black						

Dimensional characteristics



L	325 mm
L1	59 mm
H	345 mm

Lighting and photometric features

Beam opening	55°x65°
Flux	21000 lm
CCT nominal colour temperature	3000-5700 K
Colour of the light	CCT
Colour rendering index	80
Lifespan	50000 h
LED lifespan	L70B20

Electrical characteristics

Rated power	150 W
Input voltage	220-240 Vac
Frequency	50-60 Hz
Dimmable	No
Power factor (PF)	0.9
Weighted energy consumption	150 kWh/1000h
Operating temperature	-25°C / +40°C

Photometry

EulumDat file on the site

Other Infotech

Flicker Free	Yes
--------------	-----

LED Warranty

G5h24	Full Guarantee 5 years (24h/24h) Without limitations on the duration of use for the first year, provided the observance of the installation conditions.
-------	---

European Directives

2009/125/EC * Ecodesign
2011/65/EU * RoHS
2012/19/EU * RAEE
2014/30/EU * EMC
2014/35/EU * LVD
2015/863 * Amending RoHS
2017/1369 * Regulation for Energy Labelling
2019/2015 * Regulation for Energy Labelling
2019/2020 * Regulation for Ecodesign
2021/340 * Amending Reg. Energy Labelling
2021/341 * Amending Reg. Ecodesign

Product standards

CEI EN 55015:2020 (+A11:2020)
CEI EN 60598-1:2022
CEI EN 60598-2-5:2016
CEI EN 61000-3-2:2019 (+A1:2021)
CEI EN 61000-3-3:2014 (+EC1:2014/+EC2:2016/+A1:2021/+A2:2022)
CEI EN 61547:2010
CEI EN 62031:2021 (+A11:2022)
CEI EN 62471:2010
IEC/TR 62471-2:2009
CEI EN 62493:2015
CEI 34-141:2014

Logistics data

Item net weight	2850 gr
Barcode single item	8011905331405
Minimum order quantity	1
Minimum packaging	1 / 1