



DIMMER DMX FOR DURASTRIP HiVOLT

Dimmer DMX for DURASTRIP HiVOLT

Can be used with ZKTPC; 300 W/CH, 3 CH.



220-240
Vac

IP20

Screws

-25°C
+35°C



Characteristic data

Input	220-240 Vac	Base	Screws	IP	20	LED Warranty	G3
-------	-------------	------	--------	----	----	--------------	----

Dimensional characteristics

L	170 mm
L1	59 mm
H	29 mm

Electrical characteristics

Input voltage	220-240 Vac
Frequency	50 Hz
Output voltage	220-240
Operating temperature	-25°C / +35°C

LED Warranty

G3	Up to 3 years (4000h/year) *4000h = 11h a day x 365 days. Without limitations on the duration of use for the first year, provided the observance of the installation conditions.
----	--

European Directives

2009/125/EC * Ecodesign
 2011/65/EU * RoHS
 2012/19/EU * RAEE
 2014/30/EU * EMC
 2015/863 * Amending RoHS
 2017/1369 * Regulation for Energy Labelling
 2019/2015 * Regulation for Energy Labelling
 2019/2020 * Regulation for Ecodesign
 2021/340 * Amending Reg. Energy Labelling
 2021/341 * Amending Reg. Ecodesign

Product standards

CEI EN 55015:2020 (+A11:2020)
 CEI EN 61000-3-2:2019 (+A1:2021)
 CEI EN 61000-3-3:2014 (+EC1:2014/+EC2:2016/+A1:2021/+A2:2022)
 CEI EN 61347-1:2016 (+A1:2021)
 CEI EN 61347-2-11:2002 (+A1:2020)
 CEI EN 61547:2010

Logistics data

Item net weight	160 gr
Barcode single item	8011905862473
Minimum order quantity	1
Minimum packaging	1 / 1