



TRIPHOSPHOR CIRCULAR DOUBLE PACK 32W/40W

Typology

Circular fluorescent lamps in a set of two pieces of different wattage.

Features

The best fluorescent and triphosphorous powders for maximum light colour control and light emission over time, good colour rendering and the excellent luminous efficiency.

A wide reliable range for installation in professional contexts such as home environments.

Ra >80




10000 h

IP20

G10q

-15°C
+35°C



Characteristic data

| | | | | | | | |
|----------|-----|------|------|----|----|----|--------|
| Dimmable | Yes | Base | G10q | IP | 20 | Tc | 6500 K |
| Ra | >80 | | | | | | |

Lighting and photometric features

| | |
|-------------------------------------|--------------|
| Flux | 2245-2950 lm |
| CCT nominal colour temperature | 6500 K |
| Colour of the light | Cool light |
| Colour rendering index | >80 |
| Lifespan | 10000 h |
| Mercury | 3,5 mg |
| Luminous Flux Maintenance at 2000h | 88 |
| Luminous Flux Maintenance at 4000h | 85 |
| Luminous Flux Maintenance at 6000h | 80 |
| Luminous Flux Maintenance at 8000h | 75 |
| Luminous Flux Maintenance at 12000h | 72 |
| Luminous Flux Maintenance at 16000h | 70 |
| Lamp survival factor at 2000h | 100 |
| Lamp survival factor at 4000h | 100 |
| Lamp survival factor at 6000h | 95 |
| Lamp survival factor at 8000h | 80 |
| Lamp survival factor at 10000h | 50 |
| Lamp survival factor at 12000h | 45 |

Electrical characteristics

| | |
|-------------------------|---------------|
| Rated power | 32-40 W |
| Dimmable | Yes |
| Energy efficiency class | G |
| Operating temperature | -15°C / +35°C |
| Operating position | 360° |

European Directives

2009/125/EC * Ecodesign
 2011/65/EU * RoHS
 2012/19/EU * RAEE
 2014/30/EU * EMC
 2014/35/EU * LVD
 2015/863 * Amending RoHS
 2017/1369 * Regulation for Energy Labelling
 2019/2015 * Regulation for Energy Labelling
 2019/2020 * Regulation for Ecodesign
 2021/340 * Amending Reg. Energy Labelling
 2021/341 * Amending Reg. Ecodesign

Product standards

CEI EN 55015:2020 (+A11:2020)
 CEI EN 61199:2012 (+A1:2014/+A2:2015)
 CEI EN 61000-3-2:2019 (+A1:2021)
 CEI EN 61000-3-3:2014 (+EC1:2014/+EC2:2016/+A1:2021/+A2:2022)
 CEI EN 61547:2010

Logistics data

| | |
|--------------------------------|---------------|
| Item net weight | 410 gr |
| Barcode single item | 8011905993252 |
| Number of pieces multiple pack | 12 |
| Minimum order quantity | 12 |
| Minimum packaging | 12 / 12 |