

## DURA TL - TRACK LIGHT

### Typology

Professional LED projectors for track mounting.

### Features

Same shape with 3 different dimensions and power choices to cover all requirements. Can be used with Eurostandard Plus tracks as well as with other brands: Staff, Nordlux, Nordic, Global, etc.

### Installation

Mounting on 3 phases electrical tracks; fixtures equipped with a safety lock to fix to the tracks.

### Material

Die-cast painted aluminium body; black or white colour.

### Power supply

Electronic driver integrated in the fixture body.

### Beam

High efficiency Ra>85 LED Chip on Board.  
Precision optics with dichroic effect lens.  
Adjustable from 0° to -90° on the vertical plane and 350° on the horizontal plane.

### Notes


Do not use with dimmer.  
TRIAC (200-250V) dimmable version on request.



### Characteristic data

Power	10 W	Beam	24°	Dimmable	No	Input	110-240 Vac
Base	Eurostandard	IP	20	Flux	900 lm	PF	0,90
Tc	4000 K	Ra	85	LED Warranty	G5h24	Axis	2200 cd
RG	RG1	Color	Black				

## Dimensional characteristics



L	95 mm
Ø	60 mm
H	167 mm


## Lighting and photometric features

Beam opening	24°
Flux	900 lm
CCT nominal colour temperature	4000 K
Colour of the light	Natural light
Colour rendering index	85
Lifespan	50000 h
LED lifespan	L70B20
Trigger time	<0,2 s
Heating time up to 60% of full efficiency	Instant Full Light

## Electrical characteristics

Rated power	10 W
Input voltage	110-240 Vac
Frequency	50-60 Hz
Dimmable	No
Power factor (PF)	0,90
Input current	0.06 A
Weighted energy consumption	10 kWh/1000h
Number of cycles	100000
Operating temperature	-25°C / +35°C

## Photometry

	4000K	H(m)	D(m)	Emax(lx)	
	Ra80		31°		
	Fixture Power	10W	1	0.55	2234
	Source Flux	900lm	2	1.10	558
	Fixture Flux	900lm	3	1.64	248
	Efficacy	90lm/W	4	2.19	140
	861865 I <sub>max</sub> =2482cd/klm	I <sub>max</sub>	2234cd	5	2.74

EulumDat file on the site

## LED Warranty

G5h24	Full Guarantee 5 years (24h/24h) Without limitations on the duration of use for the first year, provided the observance of the installation conditions.
-------	---

## European Directives

2009/125/EC \* Ecodesign  
2011/65/EU \* RoHS  
2012/19/EU \* RAEE  
2014/30/EU \* EMC  
2014/35/EU \* LVD  
2015/863 \* Amending RoHS  
2017/1369 \* Regulation for Energy Labelling  
2019/2015 \* Regulation for Energy Labelling  
2019/2020 \* Regulation for Ecodesign  
2021/340 \* Amending Reg. Energy Labelling  
2021/341 \* Amending Reg. Ecodesign

## Product standards

CEI EN 55015:2020 (+A11:2020)  
CEI EN 60598-1:2022  
CEI EN 60598-2-1:2022  
CEI EN 61000-3-2:2019 (+A1:2021)  
CEI EN 61000-3-3:2014 (+EC1:2014/+EC2:2016/+A1:2021/+A2:2022)  
CEI EN 61547:2010  
CEI EN 62031:2021 (+A11:2022)  
CEI EN 62471:2010  
IEC/TR 62471-2:2009  
CEI EN 62493:2015  
CEI 34-141:2014

## Logistics data

Item net weight	370 gr
Barcode single item	8011905861865
Number of pieces multiple pack	20
Barcode multiple pack	8011905862060
Minimum order quantity	1