



## DURALUX D

### Typology

Compact, circular and linear fluorescent lamps.

### Features

The best fluorescent and triphosphorous powders for maximum light colour control and light emission over time, good colour rendering and the excellent luminous efficiency.

A wide reliable range for installation in professional contexts such and home environments.

86,5 Vac

Ra >80



10000 h

IP20

G24d-1

-15°C  
+35°C



320°



### Characteristic data

Power	13 W	Beam	320°	Dimmable	No	Input	86,5 Vac
Base	G24d-1	IP	20	Flux	900 lm	Tc	3000 K
Ra	>80						

### Dimensional characteristics

Ø	40 mm
H	138 mm

## Lighting and photometric features

Beam opening	320°
Flux	900 lm
CCT nominal colour temperature	3000 K
Colour of the light	Warm light
Colour rendering index	>80
Lifespan	10000 h
Mercury	2,5 mg
Luminous Flux Maintenance at 2000h	93
Luminous Flux Maintenance at 4000h	90
Luminous Flux Maintenance at 6000h	88
Luminous Flux Maintenance at 8000h	85
Luminous Flux Maintenance at 12000h	81
Luminous Flux Maintenance at 16000h	80
Lamp survival factor at 2000h	100
Lamp survival factor at 4000h	95
Lamp survival factor at 6000h	80
Lamp survival factor at 8000h	70
Lamp survival factor at 10000h	50
Lamp survival factor at 12000h	45

## Electrical characteristics

Rated power	13 W
Input voltage	86,5 Vac
Frequency	50 Hz
Dimmable	No
Input current	0.175 A
Weighted energy consumption	16 kWh/1000h
Operating temperature	-15°C / +35°C
Equivalence with incandescent lamp	70
Operating position	360°

## Spectrometry



## European Directives

2009/125/EC \* Ecodesign  
 2011/65/EU \* RoHS  
 2012/19/EU \* RAEE  
 2014/30/EU \* EMC  
 2014/35/EU \* LVD  
 2015/863 \* Amending RoHS  
 2017/1369 \* Regulation for Energy Labelling  
 2019/2015 \* Regulation for Energy Labelling  
 2019/2020 \* Regulation for Ecodesign  
 2021/340 \* Amending Reg. Energy Labelling  
 2021/341 \* Amending Reg. Ecodesign

## Product standards

CEI EN 55015:2020 (+A11:2020)  
 CEI EN 61199:2012 (+A1:2014/+A2:2015)  
 CEI EN 61000-3-2:2019 (+A1:2021)  
 CEI EN 61000-3-3:2014 (+EC1:2014/+EC2:2016/+A1:2021/+A2:2022)  
 CEI EN 61547:2010

## Logistics data

Number of pieces multiple pack	50
Barcode multiple pack	8011905710460