

SINGLE-OPTIC RECESSED FIXTURE

Typology

Rectangular recessed fixture for one adjustable GU10 lamp.

Features

Widely used in retail installations, it meets the needs of those who prefer a recessed ceiling luminaire with replaceable lamps. It offers the advantage of having both multidirectional and adjustable light beams from + 15 ° to -15 ° in the vertical plane. Houses PAR16 lamps; compatible with all GU10 lamps in the Duralamp catalogue. Max 15 W.

Installation

Recessed with the special galvanised aluminium springs. Complete with GU10 lamp holder.

Material

Body in black painted aluminium with silver colour frame.



220-240
Vac

IP20 VI
IP23 VO

GU10


-25°C
+45°C



Characteristic data

Input	220-240 Vac	Base	GU10	IP	20	Optical compartment IP	23
LED Warranty	G5h24	Color	Silver gray				

Dimensional characteristics



L	110 mm
L1	110 mm
H	125 mm

Cutting hole	95x95
--------------	-------

Electrical characteristics

Input voltage	220-240 Vac
Frequency	50/60 Hz
Operating temperature	-25°C / +45°C

LED Warranty

G5h24	Full Guarantee 5 years (24h/24h) Without limitations on the duration of use for the first year, provided the observance of the installation conditions.
-------	---

European Directives

2009/125/EC * Ecodesign
 2011/65/EU * RoHS
 2012/19/EU * RAEE
 2014/30/EU * EMC
 2014/35/EU * LVD
 2015/863 * Amending RoHS
 2017/1369 * Regulation for Energy Labelling
 2019/2015 * Regulation for Energy Labelling
 2019/2020 * Regulation for Ecodesign
 2021/340 * Amending Reg. Energy Labelling
 2021/341 * Amending Reg. Ecodesign

Product standards

CEI EN 55015:2020 (+A11:2020)
 CEI EN 60598-1:2022
 CEI EN 60598-2-2:2012
 CEI EN 61000-3-2:2019 (+A1:2021)
 CEI EN 61000-3-3:2014 (+EC1:2014/+EC2:2016/+A1:2021/+A2:2022)
 CEI EN 61547:2010
 CEI EN 62031:2021 (+A11:2022)
 CEI EN 62471:2010
 IEC/TR 62471-2:2009
 CEI EN 62493:2015
 CEI 34-141:2014

Logistics data

Item net weight	295 gr
Barcode single item	8011905975845
Number of pieces multiple pack	20
Minimum order quantity	1
Minimum packaging	1 / 20

All parts of this document are Duralamp ownership. All rights reserved. This document and the included information are provided without any responsibility deriving from mistakes or omissions. No part of this document can be cut, reproduced or used without written authorization. Duralamp maintains the right to change the included data without notice due to improvements of the products