

## SLIMFLUX BL UGR - PRO

### Typology

Ultra-flat LED fixtures with lateral lighting.  
Driver NOT included, to be fitted with the suitable driver.  
Equipped with steel anti-fall safety cable.

### Features

Side heat dissipation.  
Immediate switch-on.  
Colour rendering: Ra>80.  
Do not use with dimmer.  
If you want to dim or use the multicurrent power supply dimmer.  
UGR version.  
Class II fittings.

### Installation

Possibilities include: recessed, suspended, ceiling/wall.  
Surface mounting & adjustable suspension wire kits are available as accessories.

### Material

Painted white aluminium body; anti-yellowing PS screen.

### Usage information

SLIMFLUX 60x60 panels can be used with multi-current dimming power supply, code DELT40D-M.

### Emergency

SLIMFLUX panels can be used with standby emergency kit, code KTEMR03.



220-240  
Vac

Ra >80



50000 h  
L80B20


IP20 VI  
IP43 VO

Free Wire

-20°C  
+45°C

Risk  
Group 0

UGR <19




FLICKER  
FREE



### Characteristic data

Power	28 W	Dimmable	No	Input	220-240 Vac	Base	Free Wire
IP	20	Optical compartment IP	43	Flux	3600 lm	UGR	<19
Tc	4000 K	Ra	>80	LED Warranty	G5h24	RG	RG0

### Dimensional characteristics



L	595 mm
L1	595 mm
H	35 mm

## Lighting and photometric features

Flux	3600 lm
CCT nominal colour temperature	4000 K
Colour of the light	Natural light
Colour rendering index	>80
Lifespan	50000 h
LED lifespan	L80B20
Trigger time	<0,2 s
Heating time up to 60% of full efficiency	Instant Full Light
UGR	<19

## Electrical characteristics

Rated power	28 W
Input voltage	220-240 Vac
Frequency	50-60 Hz
Dimmable	No
Max output current	700 mA
Operating temperature	-20°C / +45°C

## Other Infotech

Flicker Free	Yes
--------------	-----

## LED Warranty

G5h24	Full Guarantee 5 years (24h/24h) Without limitations on the duration of use for the first year, provided the observance of the installation conditions.
-------	---

## European Directives

2009/125/EC \* Ecodesign  
2011/65/EU \* RoHS  
2012/19/EU \* RAEE  
2014/30/EU \* EMC  
2014/35/EU \* LVD  
2015/863 \* Amending RoHS  
2017/1369 \* Regulation for Energy Labelling  
2019/2015 \* Regulation for Energy Labelling  
2019/2020 \* Regulation for Ecodesign  
2021/340 \* Amending Reg. Energy Labelling  
2021/341 \* Amending Reg. Ecodesign

## Product standards

CEI EN 55015:2020 (+A11:2020)  
CEI EN 60598-1:2022  
CEI EN 60598-2-1:2022  
CEI EN 60598-2-2:2012  
CEI EN 61000-3-2:2019 (+A1:2021)  
CEI EN 61000-3-3:2014 (+EC1:2014/+EC2:2016/+A1:2021/+A2:2022)  
CEI EN 61547:2010  
CEI EN 62031:2021 (+A11:2022)  
CEI EN 62471:2010  
IEC/TR 62471-2:2009  
CEI EN 62493:2015  
CEI 34-141:2014

## Logistics data

Item net weight	2150 gr
Number of pieces multiple pack	6
Minimum order quantity	1
Minimum packaging	1 / 6

All parts of this document are Duralamp ownership. All rights reserved. This document and the included information are provided without any responsibility deriving from mistakes or omissions. No part of this document can be cut, reproduced or used without written authorization. Duralamp maintains the right to change the included data without notice due to improvements of the products