



DECOLED PRISMA CANDLE - DIMMABLE

Typology

Particular decorative effect reproducing that of incandescent lamps.

Features

The 'incandescent' effect is recreated thanks to the reflection of a special polycarbonate lens.

220-240
Vac

Ra >80



25000 h
L70B50

IP20

B15d

-25°C
+35°C



Characteristic data

Power	5.5 W	Beam	320°	Dimmable	Yes	Input	220-240 Vac
Base	B15d	IP	20	Flux	390 lm	PF	0,50
Tc	2200 K	Ra	>80	LED Warranty	G2		

Dimensional characteristics



Ø	37 mm
H	104 mm
H Tolerance	± 3 mm

Lighting and photometric features

Beam opening	320°
Flux	390 lm
CCT nominal colour temperature	2200 K
Colour of the light	Warm light
Colour rendering index	>80
Lifespan	25000 h
LED lifespan	L70B50
Trigger time	<0,2 s
Heating time up to 60% of full efficiency	Instant Full Light
Mercury	0,0 mg

Electrical characteristics

Rated power	5.5 W
Input voltage	220-240 Vac
Frequency	50 Hz
Dimmable	Yes
Power factor (PF)	0,50
Input current	0.04 A
Weighted energy consumption	6 kWh/1000h
Number of cycles	100000
Operating temperature	-25°C / +35°C
Equivalence with incandescent lamp	35

LED Warranty

G2	Up to 2 years (4000h/year) *4000h = 11h a day x 365 days. Without limitations on the duration of use for the first year, provided the observance of the installation conditions.
----	--

Logistics data

Item net weight	50 gr
Barcode single item	8011905840631
Number of pieces multiple pack	10
Barcode multiple pack	8011905785918