



DECO LED UP ROUND - E14

Typology

Immediate retro-fit of incandescent lamps, perfect replacement of opal incandescent lamps, no more available on the European market.

Features

Uniformly diffused lighting on the axes.

Material

The body of the lamp is in termoconductive material to optimise heat dissipation; ultralight cover.

Beam

240° - Antiglare opal finish of the lamp cover.

Notes

Disponibili su richiesta in version 110-132V AVAILABLE UPON REQUEST.

BASIC

220-240
Vac

Ra >80





15000 h
L70B50

IP20

E14


-25°C
+35°C



Characteristic data

Power	5 W	Beam	240°	Dimmable	No	Input	220-240 Vac
Base	E14	IP	20	Flux	470 lm	PF	0,58
Tc	3000 K	Ra	>80	LED Warranty	G2		

Dimensional characteristics



Ø	45 mm
H	80 mm
H Tolerance	± 3 mm

Lighting and photometric features

Beam opening	240°
Flux	470 lm
CCT nominal colour temperature	3000 K
Colour of the light	Warm light
Colour rendering index	>80
Lifespan	15000 h
LED lifespan	L70B50
Trigger time	<0,2 s
Heating time up to 60% of full efficiency	Instant Full Light
Mercury	0 mg

Electrical characteristics

Rated power	5 W
Input voltage	220-240 Vac
Frequency	50 Hz
Dimmable	No
Power factor (PF)	0,58
Input current	0.04 A
Weighted energy consumption	5 kWh/1000h
Energy efficiency class	F
Number of cycles	100000
Operating temperature	-25°C / +35°C
Equivalence with incandescent lamp	40
Operating position	360°

LED Warranty

G2	Up to 2 years (4000h/year) *4000h = 11h a day x 365 days. Without limitations on the duration of use for the first year, provided the observance of the installation conditions.
----	--

European Directives

2009/125/EC * Ecodesign 2011/65/EU * RoHS 2012/19/EU * RAEE 2014/30/EU * EMC 2014/35/EU * LVD 2015/863 * Amending RoHS 2017/1369 * Regulation for Energy Labelling 2019/2015 * Regulation for Energy Labelling 2019/2020 * Regulation for Ecodesign 2021/340 * Amending Reg. Energy Labelling 2021/341 * Amending Reg. Ecodesign	CEI EN 55015:2020 (+A11:2020) CEI EN 60968:2016 CEI EN 61000-3-2:2019 (+A1:2021) CEI EN 61000-3-3:2014 (+EC1:2014/+EC2:2016/+A1:2021/+A2:2022) CEI EN 61547:2010 CEI EN 62031:2021 (+A11:2022) CEI EN 62471:2010 IEC/TR 62471-2:2009 CEI EN 62560:2013 (+A1:2017/+A11:2020) CEI 34-141:2014
--	--

Product standards

Logistics data

Item net weight	20 gr
Barcode single item	8011905836078
Number of pieces multiple pack	10
Barcode multiple pack	8011905781354
Minimum order quantity	10
Minimum packaging	10 / 10

All parts of this document are Duralamp ownership. All rights reserved. This document and the included information are provided without any responsibility deriving from mistakes or omissions. No part of this document can be cut, reproduced or used without written authorization. Duralamp maintains the right to change the included data without notice due to improvements of the products