



## MULTI GU10

### Typology

New generation LED lamps with COB technology.

### Features

The lens is specially designed to obtain directionality of light, a clean beam and lower glare effect.

### Material

Thermally conductive compartment for housing the electronic components: optimization of heat dissipation and greater safety for the user.

### Notes


Do not use with dimmer.



### Characteristic data

Power	7 W	Beam	50°	Dimmable	No	Input	220-240 Vac
Base	GU10	IP	20	Flux	970 lm	Axis	1100 cd
PF	0,53	Tc	6000 K	Ra	80	LED Warranty	G2

### Dimensional characteristics



Ø	50 mm
H	55 mm

## Lighting and photometric features

Beam opening	50°
Flux	970 lm
Axis	1100 cd
CCT nominal colour temperature	6000 K
Colour of the light	Cool light
Colour rendering index	80
Lifespan	25000 h
LED lifespan	L70B50
Trigger time	<0,2 s
Heating time up to 60% of full efficiency	Instant Full Light
Mercury	0 mg

## Electrical characteristics

Rated power	7 W
Input voltage	220-240 Vac
Frequency	50 Hz
Dimmable	No
Power factor (PF)	0,53
Input current	0.057 A
Weighted energy consumption	7 kWh/1000h
Energy efficiency class	D
Operating temperature	-25°C / +35°C
Equivalence with incandescent lamp	117
Operating position	360°

## Other Infotech

Reflector	Yes
-----------	-----

## LED Warranty

G2	Up to 2 years (4000h/year) *4000h = 11h a day x 365 days. Without limitations on the duration of use for the first year, provided the observance of the installation conditions.
----	--

## European Directives

2009/125/EC \* Ecodesign  
2011/65/EU \* RoHS  
2012/19/EU \* RAEE  
2014/30/EU \* EMC  
2014/35/EU \* LVD  
2015/863 \* Amending RoHS  
2017/1369 \* Regulation for Energy Labelling  
2019/2015 \* Regulation for Energy Labelling  
2019/2020 \* Regulation for Ecodesign  
2021/340 \* Amending Reg. Energy Labelling  
2021/341 \* Amending Reg. Ecodesign

## Product standards

CEI EN 55015:2020 (+A11:2020)  
CEI EN 60968:2016  
CEI EN 61000-3-2:2019 (+A1:2021)  
CEI EN 61000-3-3:2014 (+EC1:2014/+EC2:2016/+A1:2021/+A2:2022)  
CEI EN 61547:2010  
CEI EN 62031:2021 (+A11:2022)  
CEI EN 62471:2010  
IEC/TR 62471-2:2009  
CEI EN 62560:2013 (+A1:2017/+A11:2020)  
CEI 34-141:2014

## Logistics data

Item net weight	36 gr
Barcode single item	8011905847906
Number of pieces multiple pack	10
Barcode multiple pack	8011905847913
Minimum order quantity	10
Minimum packaging	10 / 10