



## HELIOS IP65 CCT

### Typology

High efficiency SMD LED sources LED source integrated in a Class III, IP65, Ra90, 50000 hours downlight fixture.

Luminaire with the possibility of selecting the colour temperature at the time of installation.

### Features

IP65 fixture both optical/front side and the back/ component side; IP20 remote driver included in the package.

Soft satin effect polycarbonate anti-glare diffuser.

Remote power supply equipped with a dip-switch to select the colour temperature.

### Installation

Complete with springs for easy fastening into false ceilings.


Cable (1 m) with IP65 quick connector.

### Material

Aluminium finned dissipation body.

### Notes

Providing greater visual comfort, improved definition of detail and reduction of stress.



220-240  
Vac

Ra >90



50000 h  
L70B20

IP65

Free Wire

-25°C  
+45°C

Risk  
Group 1




FLICKER  
FREE



### Characteristic data

Power	7 W	Beam	90°	Dimmable	No	Input	220-240 Vac
Base	Free Wire	IP	65	Flux	560 lm	Axis	250 cd
PF	0,55	Tc	3000-4000-6000 K	Ra	>90	LED Warranty	G5h24
RG	RG1						

## Dimensional characteristics



Ø	100 mm
H	51 mm

Cutting hole	85
--------------	----

## Lighting and photometric features

Beam opening	90°
Flux	560 lm
Axis	250 cd
CCT nominal colour temperature	3000-4000-6000 K
Colour of the light	CCT
Colour rendering index	>90
Lifespan	50000 h
LED lifespan	L70B20
Trigger time	<0,2 s
Heating time up to 60% of full efficiency	Instant Full Light

## Electrical characteristics

Rated power	7 W
Input voltage	220-240 Vac
Frequency	50/60 Hz
Dimmable	No
Power factor (PF)	0,55
Weighted energy consumption	7 kWh/1000h
Number of cycles	100000
Operating temperature	-25°C / +45°C

## Photometry

	4000K	H(m)	D(m)	E <sub>max</sub> (lx)		
	Ra90		94°			
	Fixture Power	7W	1	2.14	246	
	Source Flux	560lm	2	4.28	62	
	Fixture Flux	560lm	3	6.42	27	
	Efficacy	80lm/W	4	8.56	15	
941260	I <sub>max</sub> =439cd/klm	I <sub>max</sub>	246cd	5	10.70	10

EulumDat file on the site

## Other Infotech

Flicker Free	Yes
--------------	-----

## LED Warranty

65h24	Full Guarantee 5 years (24h/24h) Without limitations on the duration of use for the first year, provided the observance of the installation conditions.
-------	---

## European Directives

2009/125/EC \* Ecodesign  
2011/65/EU \* RoHS  
2012/19/EU \* RAEE  
2014/30/EU \* EMC  
2014/35/EU \* LVD  
2015/863 \* Amending RoHS  
2017/1369 \* Regulation for Energy Labelling  
2019/2015 \* Regulation for Energy Labelling  
2019/2020 \* Regulation for Ecodesign  
2021/340 \* Amending Reg. Energy Labelling  
2021/341 \* Amending Reg. Ecodesign

## Product standards

CEI EN 55015:2020 (+A11:2020)  
CEI EN 60598-1:2022  
CEI EN 60598-2-2:2012  
CEI EN 61000-3-2:2019 (+A1:2021)  
CEI EN 61000-3-3:2014 (+EC1:2014/+EC2:2016/+A1:2021/+A2:2022)  
CEI EN 61547:2010  
CEI EN 62031:2021 (+A11:2022)  
CEI EN 62471:2010  
IEC/TR 62471-2:2009  
CEI EN 62493:2015  
CEI 34-141:2014

## Logistics data

Item net weight	240 gr
Barcode single item	8011905941260
Number of pieces multiple pack	36
Barcode multiple pack	8011905943769
Minimum order quantity	1