



STARGAZER - G19

Typology

Decorative LED G19 globe.

Features

Extremely bright effect thanks to the peculiar spatial arrangement of 5 LED sources inside the 60 mm transparent bulb.
Warm color temperature, ideal for cozy environments.
Extremely low energy consumption.

Material

Glass bulb.

Emergency

Ideal use in festoons.

Notes

Available with E27 and E26 base.
Do not use with dimmers.

BASIC

120 Vac

Ra >55



IP20

E26


-25°C
+35°C



Characteristic data

Power	0.8 W	Beam	300°	Dimmable	Yes	Input	120 Vac
Base	E26	IP	20	Flux	15 lm	PF	0,3
Tc	2200 K	Ra	>55	LED Warranty	G2		

Dimensional characteristics



Ø	60 mm
H	83 mm

Lighting and photometric features

Beam opening	300°
Flux	15 lm
CCT nominal colour temperature	2200 K
Colour of the light	Warm light
Colour rendering index	>55
Trigger time	<0,2 s
Heating time up to 60% of full efficiency	Instant Full Light
Mercury	0 mg

Electrical characteristics

Rated power	0.8 W
Input voltage	120 Vac
Dimmable	Yes
Power factor (PF)	0,3
Weighted energy consumption	1 kWh/1000h
Operating temperature	-25°C / +35°C
Operating position	360°

LED Warranty

G2	Up to 2 years (4000h/year) *4000h = 11h a day x 365 days. Without limitations on the duration of use for the first year, provided the observance of the installation conditions.
----	--

European Directives

2009/125/EC * Ecodesign
2011/65/EU * RoHS
2012/19/EU * RAEE
2014/30/EU * EMC
2014/35/EU * LVD
2015/863 * Amending RoHS
2017/1369 * Regulation for Energy Labelling
2019/2015 * Regulation for Energy Labelling
2019/2020 * Regulation for Ecodesign
2021/340 * Amending Reg. Energy Labelling
2021/341 * Amending Reg. Ecodesign

Product standards

CEI EN 55015:2020 (+A11:2020)
CEI EN 60968:2016
CEI EN 61000-3-2:2019 (+A1:2021)
CEI EN 61000-3-3:2014 (+EC1:2014/+EC2:2016/+A1:2021/+A2:2022)
CEI EN 61547:2010
CEI EN 62031:2021 (+A11:2022)
CEI EN 62471:2010
IEC/TR 62471-2:2009
CEI EN 62560:2013 (+A1:2017/+A11:2020)
CEI 34-141:2014

Logistics data

Item net weight	24 gr
Barcode single item	8011905981662
Number of pieces multiple pack	10
Minimum order quantity	10
Minimum packaging	10 / 10