



DECORATIVE SUSPENSION PROFILES: P06H

Features

Suspension profile.
Circular diffuser with 360° light emission.
The essential design of this profile and the 360° beam opening, allows for this profile to be installed anywhere whilst responding to many needs using the same aesthetic element.

CAN BE USED WITH LED STRIPS WITH MAXIMUM WIDTH:
30 mm

MAXIMUM POWER:
42W/m

Installation

Suspension installation.
Driver and controller must be positioned remotely to the profile.

Material

6063 aluminium profile with white polycarbonate screen.

Accessories

Every 2 metre bar is complete with 2 sets of end caps (without hole) and 2 sets of suspension cables.

Packaging


Supplied in packaging of 1 bars of 2 meters complete with screen and accessories.
Spare accessories for additional cutting available with a separate code.

Notes

Thanks to the possibility of using different strips the profile becomes a fixture that can provide different light temperatures, to be used depending on the activities carried out in that space at different times during the day.

-15°C
+35°C

Dimensional characteristics



| | |
|---|---------|
| L | 2000 mm |
| Ø | 60 mm |

Electrical characteristics

| | |
|-----------------------|---------------|
| Operating temperature | -15°C / +35°C |
|-----------------------|---------------|

European Directives

| | |
|---|--|
| 2011/65/EU * RoHS 2015/863 * Amending RoHS | |
|---|--|

Logistics data

| | |
|------------------------|---------------|
| Item net weight | 135 gr |
| Barcode single item | 8011905000844 |
| Minimum order quantity | 1 |
| Minimum packaging | 1 / 1 |