



CATENARIA

Typology

Long run conductive cable with 24 factory attached lamp holders.
Cable type: H05RR-F 300/500 V.

Features

Two different models: with lamp holder on the cable or with pendant (only 120V).
Lamp holders are fitted with IP44 protection rings.
Catenary is suitable for non-permanent outdoor installations.

Applications

Widely used for festoons indoor and outdoor garden lighting decoration, patio umbrella lighting, etc.
Suggested lamps: PING BALL, color GLS or Stargazer lamp.

Notes


Factory prepped outdoor IP44 Schuko socket for Europe, US plug or end prep wiring options for the USA.
Cannot be connected in series.



Characteristic data

Input	120 Vac	Base	E26	IP	44	LED Warranty	G2
Color	Black						

Dimensional characteristics



L	16000 mm
---	----------

Electrical characteristics

Input voltage	120 Vac
Frequency	60 Hz
Operating temperature	-25°C / +35°C

LED Warranty

G2	Up to 2 years (4000h/year) *4000h = 11h a day x 365 days. Without limitations on the duration of use for the first year, provided the observance of the installation conditions.
----	--

European Directives

2009/125/EC * Ecodesign
2011/65/EU * RoHS
2012/19/EU * RAEE
2014/30/EU * EMC
2014/35/EU * LVD
2015/863 * Amending RoHS
2017/1369 * Regulation for Energy Labelling
2019/2015 * Regulation for Energy Labelling
2019/2020 * Regulation for Ecodesign
2021/340 * Amending Reg. Energy Labelling
2021/341 * Amending Reg. Ecodesign

Product standards

CEI EN 55015:2020 (+A11:2020)
CEI EN 60598-1:2022
CEI EN 60598-2-1:2022
CEI EN 61000-3-2:2019 (+A1:2021)
CEI EN 61000-3-3:2014 (+EC1:2014/+EC2:2016/+A1:2021/+A2:2022)
CEI EN 61547:2010
CEI EN 62031:2021 (+A11:2022)
CEI EN 62471:2010
IEC/TR 62471-2:2009
CEI EN 62493:2015
CEI 34-141:2014

Logistics data

Item net weight	4000 gr
Barcode single item	8011905843830
Number of pieces multiple pack	4
Barcode multiple pack	8011905847296