



DECO LED SENSOR

Typology

LED lamp with a built-in double twilight sensor.

Features

With an automatic ON/OFF switch it remains lit from dusk to dawn with very low energy consumption.
Double sensor to improve sensitivity and to ensure it does not turn off at the wrong time.
Standby energy consumption <1W.

Material

Body in thermal plastic and aluminum embedded.

Applications

Suitable for use in transparent, clear outdoor globes.
A lamp that turns ON automatically to be used in areas that are not frequented often, ideal in gardens and entrance ways to improve personal safety.

Notes


Do not use with dimmer.
Keep this lamp away from incandescent light sources that could interfere with the correct functioning of the light sensor.



Characteristic data

Power	10 W	Beam	200°	Dimmable	No	Input	220-240 Vac
Base	E27	IP	20	Flux	1060 lm	Tc	4000 K
Ra	>80	LED Warranty	G2				

Dimensional characteristics



Ø	60 mm
H	120 mm

Lighting and photometric features

Beam opening	200°
Flux	1060 lm
CCT nominal colour temperature	4000 K
Colour of the light	Natural light
Colour rendering index	>80
Lifespan	25000 h
LED lifespan	L70B50
Trigger time	<0,2 s
Heating time up to 60% of full efficiency	Instant Full Light
Mercury	0 mg

Electrical characteristics

Rated power	10 W
Input voltage	220-240 Vac
Frequency	50 Hz
Dimmable	No
Weighted energy consumption	10 kWh/1000h
Energy efficiency class	F
Number of cycles	100000
Operating temperature	-25°C / +35°C
Equivalence with incandescent lamp	75

LED Warranty

G2	Up to 2 years (4000h/year) *4000h = 11h a day x 365 days. Without limitations on the duration of use for the first year, provided the observance of the installation conditions.
----	--

European Directives

2009/125/EC * Ecodesign
2011/65/EU * RoHS
2012/19/EU * RAEE
2014/30/EU * EMC
2014/35/EU * LVD
2015/863 * Amending RoHS
2017/1369 * Regulation for Energy Labelling
2019/2015 * Regulation for Energy Labelling
2019/2020 * Regulation for Ecodesign
2021/340 * Amending Reg. Energy Labelling
2021/341 * Amending Reg. Ecodesign

Product standards

CEI EN 55015:2020 (+A11:2020)
CEI EN 60968:2016
CEI EN 61000-3-2:2019 (+A1:2021)
CEI EN 61000-3-3:2014 (+EC1:2014/+EC2:2016/+A1:2021/+A2:2022)
CEI EN 61547:2010
CEI EN 62031:2021 (+A11:2022)
CEI EN 62471:2010
IEC/TR 62471-2:2009
CEI EN 62560:2013 (+A1:2017/+A11:2020)
CEI 34-141:2014

Logistics data

Item net weight	70 gr
Barcode single item	8011905939830
Number of pieces multiple pack	10
Barcode multiple pack	8011905958664
Minimum order quantity	10
Minimum packaging	10 / 10

All parts of this document are Duralamp ownership. All rights reserved. This document and the included information are provided without any responsibility deriving from mistakes or omissions. No part of this document can be cut, reproduced or used without written authorization. Duralamp maintains the right to change the included data without notice due to improvements of the products