




DALI / PUSH DRIVER

Features
Can be used with fittings with replaceable remote driver.
220÷240 V 50/60 Hz
Lifetime 50000 h.
Available with 100-240V voltage upon request.


220-240
Vac


DALI 2


100000 h


IP20


-20°C
+45°C





SELV












FLICKER
FREE



Characteristic data

Power	42 W	Dimmable	DALI 2	Input	220-240 Vac	IP	20
PF	0.95	LED Warranty	G5h24				

Dimensional characteristics

L	103 mm
L1	68.5 mm
H	30.5 mm

Lighting and photometric features

Lifespan	100000 h
----------	----------

Electrical characteristics

Rated power	42 W
Input voltage	220-240 Vac
Output voltage	6-38 Vdc
Dimmable	DALI 2
Power factor (PF)	0.95
Input current	0.3 A
Operating temperature	-20°C / +45°C

Other Infotech

Flicker Free	Yes
Max Case Temperature	90

LED Warranty

G5h24	Full Guarantee 5 years (24h/24h) Without limitations on the duration of use for the first year, provided the observance of the installation conditions.
-------	---

European Directives

2009/125/EC * Ecodesign
2011/65/EU * RoHS
2012/19/EU * RAEE
2014/30/EU * EMC
2014/35/EU * LVD
2015/863 * Amending RoHS
2017/1369 * Regulation for Energy Labelling
2019/2015 * Regulation for Energy Labelling
2019/2020 * Regulation for Ecodesign
2021/340 * Amending Reg. Energy Labelling
2021/341 * Amending Reg. Ecodesign

Product standards

CEI EN 55015:2020 (+A11:2020)
CEI EN 61000-3-2:2019 (+A1:2021)
CEI EN 61000-3-3:2014 (+EC1:2014/+EC2:2016/+A1:2021/+A2:2022)
CEI EN 61347-1:2016 (+A1:2021)
CEI EN 61347-2-13:2015 (+A1:2018)
CEI EN 61547:2010

Logistics data

Item net weight	180000 gr
Barcode single item	8015466162287
Minimum order quantity	1
Minimum packaging	1 / 1